
SMD ONE PORT 915 MHz SAW RESONATOR

ASR915E





> STANDARD SPECIFICATIONS:

CHARACTERISTICS			UNIT	MIN.	TYP.	MAX.	
Center Frequency Fo		MHz	914.85	915.00	915.15		
Tolerance from Fo		KHz		±150			
Insertion Loss			dB	-	1.5	3.0	
Quality Factor	Unloaded		-		45,000		
	50 Ω loaded				2,100		
Temperature Stability	Turnover Temperature		°C		39.0		
	Turnover Frequency		KHz		Fo+2.7		
	Freq. Temp. Coefficient		ppm/°C ²		0.032		
Frequency Aging			ppm/year		±10		
DC Insulation Resistance			MΩ	1.0			
RF Equivalent RLC Model	Motional Resistance R ₁		Ω		28.0	40	
	Motional Inductance L ₁		μH		46.8		
	Motional Capacitance C ₁		fF		3.0		
	Shunt Capacitance C ₀		рF	1.0	1.3	1.6	
Operating temp.		°C	-40°C to +85°C				
Storage temp.		°C	-45°C to +85°C				
Max. Rating	DC voltage	DC voltage V		±10			
RF Power Dissipation		dBm	0				

Data measured with: Source Impedance: Zs=50Ω, Load Impedance: ZL=50Ω, TA=25°C Electrostatic Sensitive Device. Handle with precaution.

> TEST CIRCUIT:

Matching

network

0

50 ohm

> MARKING:

- 915R
- A ZYX

bi ∈ i

L: dB

- 18 -2

-2

-2

ABRACON IS

ISO 9001:2008

CERTIFIED

Center 915.000 MHz

(ZY: Date code Z for month from A to L; Y for year, I.e. 4 for 2004 X: Traceability code)

HBZ

2. 49


6pan 5.000 MHz

FREQUENCY RESPONSE:

(915 Frequency in MHz)

PIN NO.	CONNECTIONS
1	Input GND
2	Input
5	Output GND
6	Output
3,7	To be GNDed
4,8	Case GND

> OUTLINE DRAWING:



ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

рит

Matching

network

0

