

# ZXMP10A13F


## 100V P-CHANNEL ENHANCEMENT MODE MOSFET

### SUMMARY

$V_{(BR)DSS} = -100V$  ;  $R_{DS(on)} = 1\Omega$  ;  $I_D = -0.7A$

### DESCRIPTION

This new generation of Trench MOSFETs from Zetex utilizes a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage, power management applications.




SOT23

### FEATURES

- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- SOT23 package

### APPLICATIONS

- DC-DC Converters
- Power Management functions
- Disconnect switches
- Motor control




### ORDERING INFORMATION

DEVICE	REEL SIZE	TAPE WIDTH	QUANTITY PER REEL
ZXMP10A13FTA	7"	8mm	3000 units
ZXMP10A13FTC	13"	8mm	10000units

### DEVICE MARKING

- 7P1

### PINOUT



# ZXMP10A13F

## ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	$V_{DSS}$	-100	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current @ $V_{GS}=10V$ ; $T_A=25^\circ C$ <sup>(b)</sup>	$I_D$	-0.7	A
@ $V_{GS}=10V$ ; $T_A=70^\circ C$ <sup>(b)</sup>		-0.5	A
@ $V_{GS}=10V$ ; $T_A=25^\circ C$ <sup>(a)</sup>		-0.6	A
Pulsed Drain Current <sup>(c)</sup>	$I_{DM}$	-3.1	A
Continuous Source Current (Body Diode) <sup>(b)</sup>	$I_S$	-1.1	A
Pulsed Source Current (Body Diode) <sup>(c)</sup>	$I_{SM}$	-3.1	A
Power Dissipation at $T_A=25^\circ C$ <sup>(a)</sup>	$P_D$	625	mW
Linear Derating Factor		5	mW/ $^\circ C$
Power Dissipation at $T_A=25^\circ C$ <sup>(b)</sup>	$P_D$	806	mW
Linear Derating Factor		6.4	mW/ $^\circ C$
Operating and Storage Temperature Range	$T_J, T_{stg}$	-55 to +150	$^\circ C$

## THERMAL RESISTANCE


PARAMETER	SYMBOL	VALUE	UNIT
Junction to Ambient <sup>(a)</sup>	$R_{\theta JA}$	200	$^\circ C/W$
Junction to Ambient <sup>(b)</sup>	$R_{\theta JA}$	155	$^\circ C/W$

### NOTES

- (a) For a device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.  
 (b) For a device surface mounted on FR4 PCB measured at  $t \leq 5$  sec.  
 (c) Repetitive rating 25mm x 25mm FR4 PCB,  $D = 0.02$ , pulse width 300 $\mu s$  - pulse width limited by maximum junction temperature.

# ZXMP10A13F

## CHARACTERISTICS



ISSUE 1 - MARCH 2005

# ZXMP10A13F

## ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated)


PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
STATIC						
Drain-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	-100			V	I <sub>D</sub> = -250μA, V <sub>GS</sub> =0V
Zero Gate Voltage Drain Current	I <sub>DSS</sub>			-1.0	μA	V <sub>DS</sub> = -100V, V <sub>GS</sub> =0V
Gate-Body Leakage	I <sub>GSS</sub>			100	nA	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V
Gate-Source Threshold Voltage	V <sub>GS(th)</sub>	-2.0		-4.0	V	I <sub>D</sub> = -250μA, V <sub>DS</sub> =V <sub>GS</sub>
Static Drain-Source On-State Resistance <sup>(1)</sup>	R <sub>DS(on)</sub>			1	Ω	V <sub>GS</sub> = -10V, I <sub>D</sub> = -0.6A
				1.45	Ω	V <sub>GS</sub> = -6V, I <sub>D</sub> = -0.5A
Forward Transconductance <sup>(1)(3)</sup>	g <sub>fs</sub>		1.2		S	V <sub>DS</sub> = -15V, I <sub>D</sub> = -0.6A
DYNAMIC <sup>(3)</sup>						
Input Capacitance	C <sub>iss</sub>		141		pF	V <sub>DS</sub> = -50V, V <sub>GS</sub> =0V f=1MHz
Output Capacitance	C <sub>oss</sub>		13.1		pF	
Reverse Transfer Capacitance	C <sub>rss</sub>		10.8		pF	
SWITCHING <sup>(2) (3)</sup>						
Turn-On Delay Time	t <sub>d(on)</sub>		1.6		ns	V <sub>DD</sub> = -50V, I <sub>D</sub> = -1A R <sub>G</sub> ≅ 6.0Ω, V <sub>GS</sub> = -10V
Rise Time	t <sub>r</sub>		2.1		ns	
Turn-Off Delay Time	t <sub>d(off)</sub>		5.9		ns	
Fall Time	t <sub>f</sub>		3.3		ns	
Gate Charge	Q <sub>g</sub>		1.8		nC	V <sub>DS</sub> = -50V, V <sub>GS</sub> = -5V I <sub>D</sub> = -0.6A
Total Gate Charge	Q <sub>g</sub>		3.5		nC	V <sub>DS</sub> = -50V, V <sub>GS</sub> = -10V I <sub>D</sub> = -0.6A
Gate-Source Charge	Q <sub>gs</sub>		0.6		nC	
Gate-Drain Charge	Q <sub>gd</sub>		1.6		nC	
SOURCE-DRAIN DIODE						
Diode Forward Voltage <sup>(1)</sup>	V <sub>SD</sub>		-0.85	-0.95	V	T <sub>J</sub> =25°C, I <sub>S</sub> = -0.75A, V <sub>GS</sub> =0V
Reverse Recovery Time <sup>(3)</sup>	t <sub>rr</sub>		29		ns	T <sub>J</sub> =25°C, I <sub>S</sub> = -0.9A,
Reverse Recovery Charge <sup>(3)</sup>	Q <sub>rr</sub>		31		nC	di/dt=100A/μs

### NOTES

- (1) Measured under pulsed conditions. Pulse width  $\leq 300\text{ms}$ ; duty cycle  $\leq 2\%$ .  
(2) Switching characteristics are independent of operating junction temperature.  
(3) For design aid only, not subject to production testing.

# ZXMP10A13F


## TYPICAL CHARACTERISTICS



ISSUE 1 - MARCH 2005


# ZXMP10A13F

## TYPICAL CHARACTERISTICS




# ZXMP10A13F

## PACKAGE OUTLINE



## PAD LAYOUT



Controlling dimensions are in millimetres. Approximate conversions are given in inches

## PACKAGE DIMENSIONS

DIM	MILLIMETRES		INCHES		DIM	MILLIMETRES		INCHES	
	MIN	MAX	MIN	MAX		MIN	MAX	MIN	MAX
A	2.67	3.05	0.105	0.120	H	0.33	0.51	0.013	0.020
B	1.20	1.40	0.047	0.055	K	0.01	0.10	0.0004	0.004
C	—	1.10	—	0.043	L	2.10	2.50	0.083	0.0985
D	0.37	0.53	0.015	0.021	M	0.45	0.64	0.018	0.025
F	0.085	0.15	0.0034	0.0059	N	0.95 NOM		0.0375 NOM	
G	1.90 NOM		0.075 NOM		Θ	10° TYP		10° TYP	

© Zetex Semiconductors plc 2005

Europe	Americas	Asia Pacific	Corporate Headquarters
Zetex GmbH Streitfeldstraße 19 D-81673 München Germany  Telephone: (49) 89 45 49 49 0 Fax: (49) 89 45 49 49 49 <a href="mailto:europe.sales@zetex.com">europe.sales@zetex.com</a>	Zetex Inc 700 Veterans Memorial Hwy Hauppauge, NY 11788 USA  Telephone: (1) 631 360 2222 Fax: (1) 631 360 8222 <a href="mailto:usa.sales@zetex.com">usa.sales@zetex.com</a>	Zetex (Asia) Ltd 3701-04 Metroplaza Tower 1 Hing Fong Road, Kwai Fong Hong Kong  Telephone: (852) 26100 611 Fax: (852) 24250 494 <a href="mailto:asia.sales@zetex.com">asia.sales@zetex.com</a>	Zetex Semiconductors plc Zetex Technology Park Chadderton, Oldham, OL9 9LL United Kingdom  Telephone (44) 161 622 4444 Fax: (44) 161 622 4446 <a href="mailto:hq@zetex.com">hq@zetex.com</a>

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to [www.zetex.com](http://www.zetex.com)

ISSUE 1 - MARCH 2005

