


[English](#) [日本語](#)
Electronics
a vital part of your world
**Find
Answers:**

Wednesday, 5 October, 2005

CATALOG

 → [Cross Reference](#)
[Competitive Products](#)
[Military Spec P/Ns](#)
[Tyco Brand P/Ns](#)

 → [Part Number Search](#)

 → [Document Search](#)

 → [Product Type Search](#)

 → [Product Family Search](#)

 → [Alphabetical Search](#)

 → [RoHS/ELV Compliance &](#)
[Alternates](#)

 → [CAD Model Search](#)

 → [Brand Search](#)

 → [Tool Search](#)

 → [Multiple Part Comparison](#)

 → [Lead Free Solutions](#)

 → [Help/Glossary](#)
[Home](#)

 e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Circuit Protection Devices
↳ PolySwitch Resettable Devices
Raychem TR250-120  [Active](#)
**Directive 2000/53/EC
Compliant**
[ELV Compliant](#)
(Corporate P/N: 018960-000)
[Search for Compliant \(RoHS/ELV\)](#)
[Alternates](#)
[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ↳ General Info ↳ Sales Info 	<ul style="list-style-type: none"> ↳ Pricing ↳ Product Availability 	<ul style="list-style-type: none"> ↳ Tooling

Searchable Features:

Brand:	Raychem
RoHS/ELV Compliance:	ELV compliant
Lead Free Solder Processes:	Wave solder capable to 240°C, Wave solder capable to 265°C
Application:	Telecom
Family Name:	TR250
Construction:	Through Hole
IH (Room Temperature) (Amps.):	0.12

Other Properties:

Tripped Power Dissipation (Typical) (W):	1.00
Coating:	Coated
Lead Type:	Kinked
UL Listed:	File No. E74889
CSA File No.:	78165C
TUV Certificate No.:	R72041425
Packaging Method:	Bulk, Tape & Reel
R (Typical) ():	6.00
UL Rated Voltage (V):	60

IT (Room Temperature) (Amps.):	0.24
Operating Temperature (Max.) (°C):	85
Vmax Operating (V):	60
Rmin ():	4.00
Rmax ():	8.000
R1 Max [Post Trip] ():	16.00
Vmax Interrupt (V rms):	250
UL Rated Current (Amps.):	3

Comment:

Devices are available with 0.5 ohm resistance matching.
Designed for equipment needing to meet ITU K.20, K.21, K.45 recommendations.

[Copyright and Privacy Statement](#)

Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]