


Honeywell Sensing and Control

Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Customer Feedback

Home> Products > Toggle and Rocker Switches > TP > Product Page

2TP8-1



TP Series Rocker Switch, 2 pole, 3 position, Screw terminal, Flush Panel Mounting

Actual product appearance may vary.

Features

- Environmentally sealed
- Two and three-position pushbutton action
- Various button colors
- 1, 2, and 4-pole circuitry
- Flush panel and above panel mountings
- Temperature range: -54 °C to +71 °C [-65 °F to +160 °F]
- UL recognized, CSA certified
- CE approved

Description

TP Rocker switches may be mounted flush with panel for a low-button profile or above panel for a distinct button appearance. Buttons measure 22.1 mm x 37.1 mm [.87 in x 1.46 in]. They are removable and interchangeable, and come in transparent plastic, translucent plastic, and six colors of opaque plastic. Switches without buttons are also available, as well as separate buttons.

Supporting Documentation

- Accessory: Rocker Operator
- Terminal Identification
- Panel Cutout Drawing

Typical Applications

- Industrial machinery and equipment
- Military and commercial aviation
- Marine applications
- Construction equipment
- Test instruments
- Agricultural machinery
- Process control
- Medical instrumentation

My Links

- Login to ICOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

Keyword Search

Search for product and support information.

Product Search

Part number search:

→ Specification Search

Product Specifications	
Product Type	Rocker
Ampsere/Voltage Range (Resistive Load)	0.5 A at 250 Vdc, 0.5 A to 20 A at 0.5 Vdc to 28 Vdc, 0.5 A to 15 A at 0.5 Vac to 277 Vac, 0.75 A at 115 Vdc
Circuitry	DPDT
Action	3 position
Circuitry/Operating action	129174
Mounting	Flush Panel
Termination	Screw
Button Type	No button
UL/CSA Rating Code	L191: 15 A-125, 250, 277 Vac; 1/2 Hp-125 Vac; 1 Hp-250, 277 Vac; 5 A-120 Vac "L"

http://sensing.honeywell.com/index.cfm?ci_id=140301&lu_id=1&pe_id=129173

Comment	Silver cadmium oxide contacts
Availability	Global
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Series Name	TP

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)

http://sensing.honeywell.com/index.cfm?ci_id=140301&lu_id=1&pe_id=129173 (2 of 2)2007-04-11 5:57:14.MD