


Home > Products > MICRO SWITCH™ Sealed and High Accuracy Switches > AT > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

68AT11-7



Actual product appearance may vary.

AT Series Toggle Switch, 8 pole, 3 position, Solder T2 type terminal, Standard Lever

Features

- Gold or silver contacts
- Choice of sealed bushing
- Standard or pull to unlock toggle lever
- Short behind-panel depth
- Solder or quick connect termination
- 2,4, 6, or 8 SPDT precision basic switches
- 2 or 3 position, momentary or maintained action

Potential Applications

- Industrial machinery and equipment
- Military and commercial aviation
- Construction equipment
- Test instruments
- Agricultural machinery
- Process control
- Medical instrumentation

Description

Compact multipole 2, 4, 6, or 8 SPDT design. MICRO SWITCH™ precision basic switches conserve space and weight. Pull -to-Unlock Toggle Levers prevent accidental operation: the lever must be pulled approximately 2,3 mm [0.09 inches] to change the positions. Many locking configurations are available. Lever to bushing seals. Hermetic basic switches are available. AT qualified versions meet MILS-8805/98. Various levers and styles are available.

Supporting Documentation

- [Accessory: Lever Sleeve](#)
- [Panel Cutout](#)
- [Accessory: Seals](#)
- [Accessory: Nuts](#)
- [Engineering Drawing](#)

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

[Specification Search](#)

Product Specifications			
Circuitry/Operating action	Keyway	Center	Opposite Keyway
	Momentary	Maintained	Momentary
	NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO
	NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO
	NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO
NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	
NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	
NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	
NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	NC COM NO NC COM NO NC COM NO	
Product Type	MICRO SWITCH™ Toggle		
Ampere/Voltage Range (Resistive Load)	0.1 A to 7.0 A at 0.5 Vdc to 28 Vdc		
Circuitry	8PDT		
Action	3 position		
Mounting	Bushing 15/32 in		
Termination	Solder T2 type		
Comment	Contains SX basic switches		
Availability	Global		
UNSPSC Code	30211908		
UNSPSC Commodity	30211908 Toggle switches		
Series Name	AT		