

[Skip to content](#)

Search By: Part Number Text [Tips](#)



Thursday, April 27, 2006

[Sign In](#)

[Home](#) > [Products](#) > [By Type](#) > [PolySwitch Resettable Devices](#) > [Product Feature Selector](#) > Product Details

Product Details for MINISMDC020F-2



MINISMDC020F-2

Tyco Part Number: C32508-000

[Active](#)

PolySwitch Resettable Devices

[RoHS Compliant](#)

Product Highlights:

- Surface Mount Application
- Family Name = miniSMD
- Surface Mount Construction
- IH (Room Temperature) = .2 Amps.
- IT (Room Temperature) = .40 Amps.

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [miniSMDC020F](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- UL Listed = 191099-E74889

Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps.\)](#) = 0.2
- [IT \(Room Temperature\) \(Amps.\)](#) = 0.40
- [Vmax Operating \(V\)](#) = 30
- [Rmin \(\)](#) = 0.60
- [R1 Max \[Post Trip\] \(\)](#) = 3.30
- [UL Rated Current \(Amps.\)](#) = 10
- Tripped Power Dissipation (Typical) (W) = 0.80

Termination Related Features:

- Construction = Surface Mount

Body Related Features:

- CSA File No. = 1031175 (CA 78165-1)

Contact Related Features:

- Application = Surface Mount
- Family Name = miniSMD

Configuration Related Features:

- [Form Factor \(inches\)](#) = 1812
- [Form Factor \(mm\)](#) = 4532

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041438

Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

Packaging Related Features:

- Packaging Method = Tape & Reel

Other:

- Brand = Raychem

Languages: English | [Deutsch](#) | [Español](#) | [Português \(do Brasil\)](#) | [Italiano](#) | [正體中文 \(繁體\) \(Chinese\)](#) | [中文 \(•体\) \(Simplified Chinese\)](#) | [日本語 \(Japanese\)](#)

Country Sites: [China](#) | [Japan](#)

© 2006 Tyco Electronics All Rights Reserved

[Home](#) | [Customer Support](#) | [Supplier](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)