Resources

My Account

Customer Support

Home > Products > By Type > PolySwitch Resettable Devices > Product Feature Selector > Product Details

NANOSMDC050F/13.2-2 Product Details



PolySwitch Resettable Devices

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Surface Mount Application
- Family Name = nanoSMD
- Surface Mount Construction
- IH (Room Temperature) = .5 Amps.
- IT (Room Temperature) = 1.10 Amps.

View all Features

Quick Links

Check Pricing & Availability
Search for Tooling Product Feature
Selector
Contact Us About This Product

2Raychem Part Number: A40202-000

NANOSMDC050F/13.2-

hem Part Number: A40202-000

Active

Documentation & Additional Information

Product Drawings:

nanoSMDC050F/13.2 (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

• None Available

Additional Information:

Product Line Information

Related Products:

Tooling

<u>List all Documents</u>

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

• UL Recognized = 271102-E74889

Electrical Characteristics:

- IH (Room Temperature) (Amps.) = 0.5
- IT (Room Temperature) (Amps.) = 1.10
- Vmax Operating (V) = 13.2
- Rmin(?) = 0.20
- R1 Max [Post Trip] (?) = 0.80
- <u>UL Rated Current (Amps.)</u> = 100
- Tripped Power Dissipation (Typical) (W) = 0.80

Termination Related Features:

• Construction = Surface Mount

Body Related Features:

• CSA File No. = 1175719 (CA 78165)

Contact Related Features:

• Family Name = nanoSMD

Configuration Related Features:

- Form Factor (inches) = 1206
- Form Factor (mm) = 3216

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041439

Conditions for Usage:

• Operating Temperature (Max.) (°C) = 85

Operation/Application:

Application = Surface Mount

Packaging Related Features:

• Packaging Method = Tape & Reel

Other

• Brand = Raychem

Provide Website Feedback | Contact Customer Support