

This document was generated on 01/11/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| | | Connector, with MS/MS-Pro/SD/MMC Functions, Bottom Mount, (.165") Height, Non Push-Push Type, Lead Free | Se Co |
|--|--|--|---|
| Documents: Drawing (PDF) | | | |
| General | | | AL A |
| Product Family Series | | Memory Card Sockets <u>47265</u> | Seri image - Reference only |
| Component Type Product Name Style | | Header & Ejector (Host) Combo, Memory Stick, MultiMediaCard, SD Card Push-Push | EU RoHS ELV and RoHS Compliant |
| Type Physical | | N/A | REACH SVHC Contains SVHC: No |
| Card Detection Switch Circuits (Loaded) | | Open 19 | Low-Halogen Status |
| Circuits (maximum) Durability (mating cycles max) Ejector Button | | 19 10,000 No | Need more information on product environmental compliance? |
| Éjector Button Side Entry Angle | | N/A 90° Angle (Side Entry) Yes | Email <u>productcompliance@molex.com</u> For a multiple part number RoHS Certificate |
| Keying to Mating Part PCB Locator PCB Mounting Side | | Yes Reverse | Compliance, <u>click here</u> Please visit the <u>Contact Us</u> section for any |
| PCB Retention PCB Thickness - Recommended Packaging Type | | Yes 1.20mm (.047") Embossed Tape on Reel | non-product compliance questions. |
| Pitch - Mating Interface Pitch - Termination Interface Ports | | 1.50mm (.059 ["]), 2.50mm (.098") 1.50mm (.059"), 2.50mm (.098") 1 | Search Parts in this Series 47265Series |
| Surface Mount Compatible (SMC) Temperature Range - Operating | | Yes -25°C to +85°C | Mates With |
| Electrical | | | SD Card MultiMedia Card MS Card |
| Current - Maximum per Contact Shielded Voltage - Maximum | | 0.5A Yes 5V | |
| Material Info | | - | |
| Reference - Drav Product Specificatior Sales Drawing | | PS-47265-001 SD-47265-001 | |

This document was generated on 01/11/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION