



(2,00mm) .0787"

FCT, EMT SERIES

FLEXCARD™ TERMINAL & SOCKET STRIPS

Mates with:
EMT

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?FCT

Insulator Material:
Black Liquid Crystal Polymer



Terminal Material:
Phosphor Bronze

Current Rating:
3A @ 80°C ambient

Operating Temp Range:
-55°C to +105°C with Tin;
-55°C to +125°C with Gold

Plating:
Sn or Au over
50µ" (1,27µm) Ni

RoHS Compliant:
Yes

Processing:
Lead-Free Solderable:
Wave, or reflow with
Matte Sn plating

Note: Some lengths, styles and options are non-standard, non-returnable.

FCT	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	D	CARD SLOT	TAIL OPTION	SL									
		20, 30 & 40 (Call Samtec for other sizes)	Specify LEAD STYLE from chart	<p>-F = Gold flash on post, Matte Tin on tail</p> <p>-L = 10µ" (0,25µm) Gold on post, Matte Tin on tail</p> <p>-S = 30µ" (0,76µm) Gold on post, Matte Tin on tail</p>		-01 = Accepts (0,80mm) .031" thick card	-RA = Right Angle (Leave blank for vertical version. Style -02 only)										
		<p>No. of positions x (2,00) .0787 + (18,19) .716</p> <p>No. of positions x (2,00) .0787 + (13,87) .546</p>		<p>(2,00) .0787</p> <p>(3,20) .126</p> <p>(2,00) .0787</p> <p>(44,45) 1.750</p>		<p>(2,00) .0787</p> <p>(1,14) .045</p> <p>(2,29) .090</p> <p>(38,10) 1.500</p> <p>(1,52) .060 TYP</p> <p>(2,54) .100 DIA TYP</p>											
		<p>Style -02</p> <p>Style -03</p>		<p>-RA OPTION</p>		<table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>Y</th> <th>CARD-TO-BOARD SPACE (X)</th> </tr> </thead> <tbody> <tr> <td>-02</td> <td>(6,35) .250</td> <td>(2,60) .1025</td> </tr> <tr> <td>-03</td> <td>(9,53) .375</td> <td>(5,78) .2275</td> </tr> </tbody> </table>		LEAD STYLE	Y	CARD-TO-BOARD SPACE (X)	-02	(6,35) .250	(2,60) .1025	-03	(9,53) .375	(5,78) .2275	
LEAD STYLE	Y	CARD-TO-BOARD SPACE (X)															
-02	(6,35) .250	(2,60) .1025															
-03	(9,53) .375	(5,78) .2275															

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?EMT

Insulator Material:
Black LCP



Contact Material:
BeCu

Current Rating:
3A @ 80°C ambient

Operating Temp Range:
-55°C to +125°C

Plating:
Sn or Au over
50µ" (1,27µm) Ni

Contact Resistance:
10 mΩ max

Insertion Depth:
(3,05mm) .120" to
(3,30mm) .130"

Insertion Force:
-01=1.5oz (0,44N) average
-51=2.5oz (0,70N) average

Withdrawal Force:
-01=1.1oz (0,31N) average
-51=1.5oz (0,44N) average

Lead-Free Solderable:
Yes, with Matte Sn plating

SMT Lead Coplanarity:
(0,10mm) .004" max (20)
(0,15mm) .006" max (30-40)

RoHS Compliant:
Yes

EMT	1	NO. PINS PER ROW	CARD THICKNESS	PLATING OPTION	D
		20, 30, 40 (Call Samtec for other sizes)	<p>-01 = (0,80mm) .031" thick board (Low Insertion Force)</p> <p>-51 = (0,80mm) .031" thick board (Standard Insertion Force)</p>	<p>-L = 10µ" (0,25µm) Gold on contact, Matte on tail</p> <p>-S = 30µ" (0,76µm) Gold on contact, Matte Tin on tail</p>	
		<p>No. of positions x (2,00) .0787 + (3,56) .140</p>		<p>(2,08) .082</p> <p>(2,00) .0787</p> <p>(2,00) .0787</p> <p>(4,00) .158</p> <p>(5,46) .215</p> <p>(3,56) .140</p> <p>(2,74) .108</p> <p>(0,81) .032</p>	
		<p>TIGER EYE CONTACT™</p>		<p>Due to technical progress, all designs, specifications and components are subject to change without notice.</p>	

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 8990337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292 SAMTEC ISRAEL • Tel: 972-3-7526600
 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-61103766 SAMTEC TAIWAN • Tel: 886-2-2735-6109
 Downloaded from Elcodis.com electro SAMTEC HONG KONG • Tel: 852-2600-9858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9512 7747 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112