() IDT	English  简体中文 日本語	Search by Part Number		Search by Keyword(s)	
	Contact IDT   Investors   Press	About IDT Produ	cts Applications	Support myIDT	
Calculators   Cross Reference   Green Ini	tiative   Parametric Search   Search by Part Number Ke	eyword , Document, Green/Pb	Free, Package		
Home > Products > Serial RapidIOÂ ® Solu 80KSW0005BR	titions > Central Packet Switches (CPS) > 80KSW0005 > 80	KSW0005BR		You may also like	
Category:	Central Packet Switches (CPS)			Use	
Generic Part:	80KSW0005			your time	
Description:	CENTRAL PACKET SWITCH CPS	10Q		wisely.	

Parameters		
Package	FCBGA 676	
Speed	NA	
Temperature	С	
Voltage	1.2 V	

Package

Package

## Sales and Support

Sales Offices > Sales Offices and authorized distributors Technical Support Serial RapidIO® ▶ Email:flow -controlhelp@idt.com ▶ Phone: 408:360-1740

## **Distributor Inventory**

No Pricing information is available from our Distributors at this time.

## Documents

Туре	Title	Size	Revision Date
Flyer	Functional InterConnect (FIC) Devices	1225 KB	07/14/2008
	IDT Quick Reference Guide	577 KB	09/17/2008
	Serial RapidIO (SRIO) Family Flyer	133 KB	10/17/2008
	Wireless Infrastructure Solutions Flyer	214 KB	10/17/2008
Product Brief	80KSW0005 (CPS10Q) Product Brief	151 KB	11/06/2008
	80KSW0006 (CPS6Q) Product Brief	99 KB	11/06/2008
	80KSW0002 (CPS16) Product Brief	62 KB	11/06/2008
	80KSW0003 (CPS8) Product Brief	67 KB	11/06/2008
	80KSW0004 (CPS12) Product Brief	61 KB	11/06/2008
Product Change Notice	PCN# : TB090106 Laser Top Mark on Selective Plastic Packages	763 KB	02/24/2009
White Paper	SRIO Whitepaper: Using 2nd and 3rd Generation sRIO Devices to Improve 3G+ Baseband Processing	247 KB	09/22/2008

 Home
 Site Map
 Legal
 Careers
 Contact Us
 Quality
 Iss

 Use of this website signifies your agreement to the
 acceptable use and privacy policy
 . Copyright
 © 1997 -2009
 Integrated Device Technology, Inc.
 All Rights Reserved.

Description	FLIP CHIP BGA 27 X 27 MM 1.0 MM PITCH
Status	Active
Class	PLASTIC
Category	RoHS
Pb (Lead) Free	No
Pb Free Category	e1 SnAgCu
Mark	BR
Package Type	FCBGA
Lead Count	676
Length	27.0 mm
Width	27.0 mm
Thickness	3.4 mm
Pitch	1.0 mm
Tube / Tray	TRAY
Quantity per Tube/Tray	40
Quantity per Reel	350
Moisture Sensitivity Level (MSL)	4
Moisture Exposure Floor Life	72 hrs@<30C/60%RH
Peak Reflow Temperature	245°C
Rebake Conditions	48hrs@125C
Related Package Documents	view documents

FCBGA 676 (BR676)