TS250-130F-B-0.5-2 Product Details - Tyco Electronics

Skip to content

<u>Corporate Home</u> | ▶ Electronic Components | <u>Segments</u> | <u>Who We Are</u>

Worldwide





Our commitment. Your advantage.

Search By:



Sign In | Register (Why Register?)

Products

Þ

Connectors

Electromechanical

Components

**Electronic Modules** 

Fiber Optics

Filters

**Identification Labeling** 

Products

Passive Components

Power Sources

RF & Microwave Products

**Tooling Products** 

Touch Screen Displays

Tubing, Molded and

Harnessing Products

Wire, Cable and Cable

Assemblies

List all Product Types



# TS250-130F-B-0.5-2 Product Details



TS250-130F-B-0.5-2

Raychem Part Number: A13328-000
Active

# **PolySwitch Resettable Devices**



Always EU RoHS/ELV Compliant (Statement of Compliance)

#### **Product Highlights:**

- Telecom Application
- Family Name = TS250
- Surface Mount Construction
- IH (Room Temperature) = .13 Amps.
- IT (Room Temperature) = .26 Amps.

View all Features

#### Quick Links

- Check
  Pricing &
  Availability
- Search for Tooling
- Product
  Feature
  Selector
- Contact Us
  About This
  Product

# **Documentation & Additional Information**

#### **Product Drawings:**

• <u>TS250-130F-B-0.5</u> (PDF, English)

# **Catalog Pages/Data Sheets:**

• None Available

# **Product Specifications:**

• None Available

# **Application Specifications:**

• None Available

#### **Instruction Sheets:**

• None Available

### **CAD Files:**

• None Available

#### **Additional Information:**

• Product Line Information

#### **Related Products:**

• Tooling

List all Documents

 $http:\!/\!(catalog.tycoelectronics.com/TE/bin/TE.Connect?\!C=\!1\&M=BYPN\&TCPN=A13328-000\&RQPN=TS250-130F-B-0.5-2\ (3\ of\ 4)26/09/2007\ 10:50:57\bullet (3\ of\ 4)26/09$ 

#### Product Features (Please use the Product Drawing for all design activity)

# **Product Type Features:**

- UL Recognized = File No. E74889
- Comment = Devices are available with 0.5 ohm resistance matching.;
   Designed for equipment needing to meet ITU K.20, K.21, K.45 recommendations.

#### **Electrical Characteristics:**

- IH (Room Temperature) (Amps.) = 0.13
- IT (Room Temperature) (Amps.) = 0.26
- $\underline{\text{Vmax Operating (V)}} = 60$
- Rmin() = 6.50
- Rmax() = 12.000
- R1 Max [Post Trip] (\_\_) = 20.00
- Vmax Interrupt (V rms) = 250
- UL Rated Current (Amps.) = 3
- Tripped Power Dissipation (Typical) (W) = 1.10
- R (Typical) ( ) = 9.25
- Resistance Matching ( ) = 0.5
- UL Rated Voltage (V) = 60

#### **Termination Related Features:**

• Construction = Surface Mount

#### **Body Related Features:**

• CSA File No. = 78165C

# **Contact Related Features:**

• Family Name = TS250

# **Configuration Related Features:**

• Coating = Uncoated

# **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041430

#### **Conditions for Usage:**

• Operating Temperature (Max.) (°C) = 85

#### **Operation/Application:**

• Application = Telecom

#### **Packaging Related Features:**

• Packaging Method = Tape & Reel

#### Other:

• Brand = Raychem

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support

© 2007 Tyco Electronics Corporation All Rights Reserved