

26.5MM UNIVERSAL WHITE

Status	Production
Part no.	10455
Drawing no.	60475
No. of optics	1
No. of legs	4
Pin length	2.0
Related Optics	10048 26.5 mm Plain Tight Catadioptic 10124 26.5 mm Frosted Narrow Catadioptic 10108 26.5 mm Frosted Medium Catadioptic 10260 26.5 mm Frosted Wide Catadioptic 10049 26.5 mm Elliptical Catadioptic 10224 26.5 mm Elliptical Orthogonal Catadioptic 10234 26.5 mm Elliptical Ramp Catadioptic 10391 26.5 mm Plain Tight Catadioptic 10392 26.5 mm Frosted Narrow Catadioptic 10393 26.5 mm Frosted Medium Catadioptic 10394 26.5 mm Frosted Wide Catadioptic 10395 26.5 mm Elliptical Catadioptic
Related LEDs	Cree XLamp® XR® Cree XLamp® XR-EA® Cree XLamp® XR-C® Cree XLamp® XP-G Cree XLamp® MX-6 Osram Dragon Golden Dragon W5SG Osram Dragon Golden Dragon W5SM Osram Dragon Platinum Dragon W5SN Osram Dragon Dragon Plus W5AM
Files	Customer drawing (PDF)



Carclo Technical Plastics endeavours to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct and up to date information, Carclo suggest using the Opticselect tool on our website <http://www.carclo-optics.com>.
Copyright © Carclo 2010

Handling instructions

- Do not handle or install lenses without wearing gloves, skin oils may damage the lens or the light transmission.
- Clean lenses with a mild soap and water and dry with a clean soft cloth.
- Do not use any commercial solvents on lenses.
- Mount holders with low Odour epoxy's and allow time for them to out gas to stop lenses fogging.

Please note that flow lines, weld lines, surface scratches and small black or white inclusions within the lenses are acceptable if the optical performance of the lens is within the specification described to +/-10%. FWHM-Full (beam) Width as measured at one Half of Maximum intensity, information shown in the catalogue are based on our laboratory's tests.

All rights reserved. No part of this publication may be copied, reproduced in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, illustrations not to be removed, without our prior permission. Carclo Technical Plastics reserves the right to make changes at any time in order to supply the best products possible.