

**20.0MM FROSTED WIDE TIR**

|                     |  |
|---------------------|--|
| <b>Status</b>       | Production                             |
| <b>Part no.</b>     | 10202                                  |
| <b>Drawing no.</b>  | 60462                                  |
| <b>Product type</b> | Optic                                  |
| <b>Type</b>         | TIR                                    |
| <b>Pieces</b>       | 1                                      |
| <b>Diameter</b>     | 20.0                                   |
| <b>Height</b>       | 9.60                                   |
| <b>Beam</b>         | Frosted Wide                           |
| <b>Flange</b>       | Yes                                    |
| <b>Files</b>        | <a href="#">Customer drawing (PDF)</a> |



| LEDs & Performances        | Eff.  | FWHM | Cd/lm | Spot | Cross-section | Files                                      |
|----------------------------|-------|------|-------|------|---------------|--|
| Cree XR® XLamp® White      | 81.0% | 35.6 | 1.8   |      |               |  |
| Cree XR-E® XLamp® White    | 84.0% | 36   | 2.0   |      |               | 10202_cree_xre_white_250408.ies            |
| Cree XR-C® XLamp® White    | 81.0% | 39   | 2.0   |      |               | 10202_Cree_XRC_White_250408.ies            |
| Avago Aveon Cool White     | 79.0% | 31.3 | 2.5   |      |               | 10202_Avago_Aveon_cool white_250408.ies    |
| Avago Moonstone Warm White | 80.6% | 39.8 | 1.4   |      |               | 10202_Avago_Moonstone_WarmWhite_250408.ies |
| Avago Moonstone RGB        | 76.7% | 38.1 | 1.4   |      |               | 10202_Avago_Moonstone_RGB_250408.IES       |

| Related Holders & LEDs                                 | Avago Aveon Cool White | Avago Moonstone RGB | Avago Moonstone Warm White | Cree XR® XLamp® White | Cree XR-C® XLamp® White | Cree XR-E® XLamp® White |
|--|------------------------|---------------------|----------------------------|-----------------------|-------------------------|-------------------------|
| 10205 20.0mm Circular Black                            |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10206 20.0mm Circular Clear                            |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10207 20.0mm Circular White                            |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10276 50.0mm Triple White                              |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10286 50.0mm Triple White                              |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10296 50.0mm Triple Black                              |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10306 50.0mm Circular Black                            |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10425 20.0mm Hexagonal Black                           |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10426 20.0mm Hexagonal Clear                           |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10427 20.0mm Hexagonal White                           |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10428 20.0mm Hexagonal Black                           |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10429 20.0mm Hexagonal Clear                           |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 10430 20.0mm Hexagonal White                           |                        |                     |                            | ✓                     | ✓                       | ✓                       |
| 47.313.5101.80 with<br>47.313.-320.80 20.0mm BJB Black |                        |                     |                            |                       | ✓                       | ✓                       |

Carclo Technical Plastics endeavours to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct and up to date information, Carclo suggest using the Opticselect tool on our website <http://www.carclo-optics.com>.

Copyright © Carclo 2010

#### Handling instructions

- Do not handle or install lenses without wearing gloves, skin oils may damage the lens or the light transmission.
- Clean lenses with a mild soap and water and dry with a clean soft cloth.
- Do not use any commercial solvents on lenses.
- Mount holders with low Odour epoxy's and allow time for them to out gas to stop lenses fogging.

Please note that flow lines, weld lines, surface scratches and small black or white inclusions within the lenses are acceptable if the optical performance of the lens is within the specification described to +/-10%. FWHM-Full (beam) Width as measured at one Half of Maximum intensity, information shown in the catalogue are based on our laboratory's tests.

All rights reserved. No part of this publication may be copied, reproduced in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, illustrations not to be removed, without our prior permission. Carclo Technical Plastics reserves the right to make changes at any time in order to supply the best products possible.