

1-66359-4

TE Internal Number: 1-66359-4

Active

Multimate

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Pin
- Bright Tin Contact Mating Area Plating Material
- Wire Range = 0.80-2.00² [18-14] mm [AWG]
- Insulation Diameter = 2.03 2.54 mm
- Brass Contact Base Material

View all Features

Documentation & Additional Information	
 Product Drawings: PIN ASSEMBLY, .062, TYPE III+ (PDF, English) 	Additional Information: • Product Line Information
Catalog Pages/Data Sheets: • <u>HIGH CURRENT PRODUCTS</u> (PDF, English)	Additional Product Images: • Line Drawing
 <u>PRECISION PIN AND SOCKET CONTACTS</u> (PDF, English) Signal Contacts (PDF, English) 	Related Products: • <u>Tooling</u>
M_SERIES_PIN_AND_SOCKET_CONNECTORS (PDF, English) CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND	
 <u>POWER</u> (PDF, English) <u>AMP Circular Connectors for Commercial Signal & Powe</u> (PDF, English) 	
Product Specifications: • None Available	
 Application Specifications: Type III + (Size 16) Contacts (PDF, English) 	
Instruction Sheets: • None Available	
CAD Files: (CAD Format & Compression Information) <u>2D Drawing</u> (DXF, Version AA1) 	
 <u>3D Model</u> (IGES, Version AA1) <u>3D Model</u> (STEP, Version AA1) 	
List all Documents	

Product Features (Please use the Product Drawing for all design activity)		
 Product Type Features: Pin/Socket = Pin Insulation Diameter (mm [in]) = 2.03 – 2.54 [0.080 – 0.100] Product Type = Type III+ Insulation Support = Yes Wire Termination Type = Crimp Wire/Cable Type = Discrete Wire Grade = Commercial Comment = Overall insulation crimp diameter, including crimp barrel, must not exceed 3.18 [.125]. Electrical Characteristics: 	 Contact Related Features: <u>Contact Mating Area Plating Material</u> = Bright Tin <u>Contact Base Material</u> = Brass <u>Contact Size</u> = 16 <u>Contact Type</u> = Signal Industry Standards: <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant <u>Lead Free Solder Processes</u> = Not relevant for lead free process RoHS/ELV Compliance History = Always was RoHS compliant 	
High Current = No	Conditions for Usage: • Terminate To = Wire	
 Termination Related Features: <u>Termination End Plating</u> = Bright Tin 	• Test Current (Amps.) = 13.0	

• Pin Diameter (mm [in]) = 1.57 [0.062]

Body Related Features:

- <u>Wire Range (mm [AWG])</u> = 0.80-2.00² [18-14]
- Spring Material = Stainless Steel
- Used With = G Series Connectors, CPC Connectors, M Series Connectors

Packaging Related Features:

<u>Packaging Method</u> = Reverse Reeled

Other:

• Brand = AMP