<u>Check Distributor Inventory</u>

Find Authorized Distributors



- о <u>Sign In</u>
- <u>Register</u>

# . Customer Support

- o <u>Support</u>
- <u>RoHS Support Center</u>
- o Glossary of Terms
- o <u>eBulletin Newsletter</u>

Home > Products > By Type > Terminal Blocks & Strips > Product Feature Selector > Product Details

# 2-1546670-0 Product Details



#### **Documentation & Additional Information**

#### Product Drawings:

• DOUBLE ROW BARRIER STRIP W/ BINDING HD SCREW, .437 S... (PDF, English)

#### Catalog Pages/Data Sheets:

• BUCHANAN TERMINAL BLOCKS CATALOG - BARRIER STRIPS (PDF, English)

#### Product Specifications:

- None Available
- Application Specifications:
  - None Available

#### Instruction Sheets:

None Available

# CAD Files:

• None Available

Additional Information:

Product Line Information

**Related Products:** 

• <u>Tooling</u>

List all Documents

#### **Product Type Features:**

- <u>Product Type</u> = Barrier Strip
- <u>Mount Angle</u> = Vertical
- <u>Mounting Ears</u> = With
- Number of Circuits = 20
- <u>Screw Material</u> = Steel
- Screw Size = 6-32 x 1/4

### **Mechanical Attachment:**

- <u>Mounting Style</u> = Open End Position
- <u>Screw Plating</u> = Nickel

## **Electrical Characteristics:**

- <u>Base Style</u> = Flat With End Mounting Holes
- <u>Number of Levels</u> = Single
- End Barriers = Without
- <u>Mounting Insert</u> = Without
- <u>Top Hardware</u> = Brass Clamp-plate Combo Head Screws
- Current Rating (Amps.) = 25

# Provide Website Feedback | Contact Customer Support Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support © 2008 Tyco Electronics Corporation All Rights Reserved

# **Body Related Features:**

- <u>Block Series</u> = Dual Barrier
- <u>Centerline (mm [in])</u> = 11.10 [0.4375]
- <u>Number of Rows</u> = 2
- Length (mm [in]) = 241.00 [9.490]
- Block Material = Thermoplastic
- Block Color = Black
- Wire Range (mm [AWG]) = 0.30-2.00<sup>2</sup> [22-14]

# Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

# Other:

• Brand = Buchanan