

8838	3100	8853	6800
8838-0-15-XX-34-XX-10-0 Solder mount in .086 min. mounting hole	3100-0-15-XX-34-XX-10-0 Solder mount in .074 min. mounting hole	8853-0-15-XX-34-XX-10-0 Press-fit in .071 mounting hole	6800-0-15-XX-34-XX-04-0 Solder mount in .080 min. mounting hole

0739	8206		
0739-0-15-XX-34-XX-10-0 Hex press-fit in .078±.002 plated thru hole	8206-0-15-XX-34-XX-40-0 Surface mount P.C.B. PAD	P.C.B. Layout 	

--	--	--	--

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 15 - XX - 34 - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <ul style="list-style-type: none"> 01 200μ" TIN/LEAD OVER NICKEL ◇ 80 200μ" TIN OVER NICKEL (RoHS) ◇ 15 10μ" GOLD OVER NICKEL (RoHS) <p>SPECIFY CONTACT FINISH:</p> <ul style="list-style-type: none"> 01 200μ" TIN/LEAD OVER NICKEL ◇ 80 200μ" TIN OVER NICKEL (RoHS) ◇ 27 30μ" GOLD OVER NICKEL (RoHS) <p style="text-align: center;">CONTACT #34 CONTACT (DATA ON PAGE 222)</p> <div style="text-align: center;"> </div>
--	--