- o Check Distributor Inventory
- Find Authorized Distributors

# . My Account

- o Sign In
- o Register

# . Customer Support

- o Support
- o RoHS Support Center
- o Glossary of Terms
- o eBulletin Newsletter

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>PCB Connectors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

**Live Product Chat** US Only

# 6-146252-3 Product Details



6-146252-3



# .100 inch AMPMODU Headers



## **Product Highlights:**

- Header
- Header Type = Breakaway
- Number of Rows = Dual
- Number of Positions = 26
- Mating Post Length = 8.08 mm

View all Features | Find Similar Products

Quick Links

- Check
  Pricing &
  Availability
- Search for Tooling
- Product
  Feature
  Selector
- Contact Us
  About This
  Product

**Documentation & Additional Information** 

## **Product Drawings:**

• None Available

# Catalog Pages/Data Sheets:

• None Available

# **Product Specifications:**

• None Available

# **Application Specifications:**

• None Available

# **Instruction Sheets:**

• None Available

## **CAD Files:**

• None Available

Additional Information:

• Product Line Information

## **Related Products:**

• Tooling

# Product Features (Please use the Product Drawing for all design activity)

# **Product Type Features:**

- Product Type = Header
- Number of Positions = 26
- Mount Angle = Vertical
- PCB Retention Feature = No
- Surface Mount Compatible = Yes
- Board Standoff = With
- Mounting Ears = Without
- Mating Connector Lock = Without
- Post Size (mm [in]) = 0.64 [.025]

#### **Mechanical Attachment:**

- Mating Post Length (mm [in]) = 8.08 [0.318]
- Panel Attachment = Without

#### **Electrical Characteristics:**

- Current Rating (Amps.) = 3
- Insulation Resistance (M•) = 5,000
- Dielectric Withstanding Voltage (V) = 750

## **Termination Related Features:**

- Termination (Solder) Post Length (mm [in]) = 3.18 [0.125]
- Solder Tail Contact Plating = Tin over Nickel, Matte Tin over Nickel

## **Body Related Features:**

- Header Type = Breakaway
- Number of Rows = Dual
- Centerline, Matrix (mm [in]) =  $2.54 \times 2.54 = [.100 \times .100]$
- Selectively Loaded = No
- Mount Type = PC Board

Provide Website Feedback | Contact Customer Support
Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support
© 2008 Tyco Electronics Corporation All Rights Reserved

#### **Contact Related Features:**

- Contact Mating Area Plating Material = Gold (15)
- Contact Shape = Square
- Contact Material = Phosphor Bronze
- Approved Standards = UL E28476, CSA LR7189

#### **Housing Related Features:**

- Housing Material = Thermoplastic
- Housing Flammability Rating = UL 94V-0

## **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

## **Conditions for Usage:**

- <u>High Temperature Housing</u> = Yes
- Operating Temperature ( $^{\circ}$ C) = -65 +105

## Operation/Application:

• High Speed Serial Data Connector = No

## Other:

• Brand = AMP