




Home About Us Products Applications Sales Support Contact Us Search

[Industrial Products](#) > [Connectors](#) > [Harsh Environment Connectors](#) > [Mini-Con-X Connectors 0.715" OD](#) > [Mini-Con-X Cable Connectors](#)



enlarge

## Mini-Con-X Cable Connectors

Utilizing a separate o-ring, Mini Con X connectors are available up to 4-#16 pins/sockets, 6-#20 pins/sockets, 5-#16 cable end socket and 7&8-#20 cable end sockets. Meets NEMA 6P when mated.

Part Builder

Specifications

Need more info? Contact Conxall customer service

[Printer friendly version](#)

### Typical Specifications

- Rating: 4.8 thru 13.0A, 600V
- Conductor Size:
  - #16 Contacts, 16 thru 18 AWG
  - #20 Contacts, 20 thru 24 AWG
- Configuration: 2 thru 5 #16 Contacts or 2 thru 8 #20 Contacts
- Certification:
  - UL Recognized File #E150822 - 600V AC/DC
  - CSA Certified File #181200 - 600V
  - U.L. Temperature 75°C max.
  - Not for current interruption

### Material Specifications

#### Cable Pin/Socket

- Backshell (Removable Twist Lock): Nylon, UL Recognized, Black
- Grommet: Santoprene Rubber, Black
- Coupling Ring: Nylon, UL Recognized, Black
- Contacts: Brass, Gold over Nickel
- Connector Body: Nylon, UL Recognized, Black
- O-Ring: Neoprene Rubber, Black

#### Optional

- Long Backshell (Removable Twist Lock): Nylon, UL Recognized, Black (Style #5)
- Winged Coupling Ring: Nylon, UL Recognized, Black (W/6482)

#### Cable to Cable

- Backshell (Removable Twist Lock): Nylon, UL Recognized, Black
- Grommet: Santoprene Rubber, Black
- Contacts: Brass, Gold over Nickel
- Connector Body: Nylon, UL Recognized, Black

#### Panel Mount

- Contacts: Brass, Gold over Nickel
- Panel Body: Nylon, UL Recognized, Black
- Gasket: Neoprene Rubber, Black

- Hex Nut: Nylon, UL Recognized, Black

**Optional**

- Dust Cap: Santoprene Rubber, Black (Part No. 6295)
- Gasket, O-Ring, & Grommet materials are suitable for storage -40°C to +90°C (-40°F to +194°F).
- Consult factory for higher temperature requirements.

**Mechanical Specifications**

- Durability: Minimum 300 mate/unmate cycles without mechanical or electrical failure
- Vibration: Coupling rings have overriding locking feature to prevent loosening or separation of connector
- Hex Nut Torque: All series hex nut to withstand 10-12 inch/lb tightening torque

**Electrical Specifications**

- Voltage: 600 V
- Current: See Electrical Current Rating Chart

**Environmental Specifications**

- Storage Temperature Rating: -40°C to +115°C (-40°F to +239°F)
- Corrosion: 300 Hr salt spray contacts
- Weathertight: Consult factory with specific application

**Molded Cable Assemblies**

- Watertight: NEMA 6P, 13: IEC IP67

5555 N Elston Ave • Chicago • Illinois • 60630 • USA • 1.773.792.2700

[Home](#) [About Us](#) [Sales](#) [Contact Us](#) [Login](#)

