

36501E6N2JTDG Product Details



36501E6N2JTDG

• Inductor

Inductors

Compliance) **Product Highlights:**

- Inductor Type = High Frequency
- Lead Type = Surface Mount Terminals

Always EU RoHS/ELV Compliant (Statement of

- Wirewound
- Inductance = $.0062 \mu H$

View all Features



Documentation & Additional Information

Product Drawings:

• LOW INDUCTANCE, HIGH FREQUENCY CHIP INDUCTOR SERIES 3650 (PDF, English)

Catalog Pages/Data Sheets:

 Low Inductance, High Frequency Chip Inductors - Type... (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

• Product Line Information

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Product Type</u> = Inductor
- Inductor Type = High Frequency
- <u>Element</u> = Wirewound
- Shielded = No

Electrical Characteristics:

- Inductance (μ H) = 0.0062
- DC Resistance (Ω) = 0.083
- Current, Maximum (mA) = 760
- Quality Factor = 20
- Package Type = Taped and Reeled
- Tolerance (%) = 5

Body Related Features:

- <u>Lead Type</u> = Surface Mount Terminals
- <u>Series</u> = 3650
- Packaging Style = 0402
- Package, Component Size = 1.5 x 0.5
- Mount Style = Surface Mount

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Operation/Application:

• Application = High Frequency

Other:

• Brand = Sigma Inductors