

## 404802692032 Product Details



404802692032

TE Internal Number: 2-1625931-6

### Variable Resistors



Converted to EU RoHS/ELV Compliant

### **Product Highlights:**

- $\begin{array}{ll} \bullet & \mbox{Variable Resistor} \\ \bullet & \mbox{Resistor Type} = \mbox{Potentiometer} \\ \bullet & \mbox{Resistance Selection} = <1\mbox{K} \; \Omega \\ \bullet & \mbox{Resistance} = 100 \; \Omega \\ \end{array}$
- Power Rating = 2.00 W



## **Documentation & Additional Information**

#### Product Drawings:

Catalog Pages/Data Sheets:
• Spindle Operated Potentiometers - Type M Series - Ty... (PDF, English)

### Product Specifications:

## Application Specifications:

None Available

## **Instruction Sheets:**

# CAD Files: (CAD Format & Compression Information) ■ 2D Drawing (DXF, Version P00K)

- <u>3D Model</u> (IGES, Version P00K)
- <u>3D Model</u> (STEP, Version P00K)

### Additional Information:

Product Line Information

## Related Products: • Tooling

# Product Features (Please use the Product Drawing for all design activity)

## Product Type Features:

- Product Type = Variable Resistor
- Resistor Type = Potentiometer
- Resistance ( $\Omega$ ) = 100 • <u>Element</u> = Cermet
- Sealed = Yes
- <u>Termination Type</u> = PCB Terminations

## **Electrical Characteristics:**

- Resistance Selection ( $\Omega$ ) = <1K
- Power Rating (W) = 2.00
- <u>Tolerance (%)</u> = 10

## **Termination Related Features:**

<u>Termination Post Orientation</u> =  $5.0 \times 3.9$ 

## Body Related Features:

- Series = M
- Shaft Style = Plain, 1"
- Package, Component Size = 19

## **Configuration Related Features:**

- Sections = Single
- Adjustment Location = Top
- Adjustment Style = Spindle
- Operating Function = Single Turn

## Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Other:
• Brand = Citec