

## SBCHE44R7K Product Details



Documentation & Additional Information	
Product Drawings: • None Available	Additional Information: • Product Line Information
Catalog Pages/Data Sheets: • <u>High Power Resistor - Type SBC (Square Ceramic) Seri</u> (PDF, English)	Related Products: • <u>Tooling</u>
<ul> <li>Product Specifications:</li> <li>None Available</li> </ul>	
Application Specifications: • None Available	
Instruction Sheets: • None Available	
CAD Files: • None Available	
List all Documents	

Product Features (Please use the Product Drawing for all design activity) Industry Standards: Product Type Features: • Product Type = Fixed Resistor • <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant • Resistor Type = Power Resistor • Lead Free Solder Processes = Wave solder • Resistance ( $\Omega$ ) = 4.7 capable to 240°C, Wave solder capable to 260°C, • <u>Element</u> = Wirewound Wave solder capable to 265°C • <u>Termination Type</u> = Tinned Copper Leads • RoHS/ELV Compliance History = Converted to comply with RoHS directive **Electrical Characteristics:** • <u>Resistance Selection ( $\Omega$ )</u> = <1K Conditions for Usage: • <u>Power Rating (W)</u> = 4.00 • <u>Temperature Coefficient (ppm/°C)</u> =  $\pm 400$ • Tolerance (%) = 10• Package Type = Loose Piece - Box **Operation/Application:** • <u>Application</u> = Power **Body Related Features:** • <u>Series</u> = SBC Other: • Mount Style = Axial Leaded • Brand = CGS Package, Component Size = 7 x 8 x 20

Downloaded from Elcodis.com electronic components distributor