

CFR16J100K Product Details



CFR16J100K

TE Internal Number: 1623927-1

 [Active](#)

Fixed Resistors

 [Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Fixed Resistor
- Resistor Type = General Purpose Resistor
- Resistance Selection = K Ω
- Resistance = 100K Ω
- Power Rating = .25 W

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)

[Request Sample](#)

[Find Similar Products](#)

[Buy Product](#)

Documentation & Additional Information	
Product Drawings: <ul style="list-style-type: none"> • CARBON FILM FIXED RESISTORS SERIES CFR16 (PDF, English) Catalog Pages/Data Sheets: <ul style="list-style-type: none"> • Ceramic Film Fixed Resistors - Type CFR Series - Tyc... (PDF, English) Product Specifications: <ul style="list-style-type: none"> • None Available Application Specifications: <ul style="list-style-type: none"> • None Available Instruction Sheets: <ul style="list-style-type: none"> • None Available CAD Files: <ul style="list-style-type: none"> • None Available 	Additional Information: <ul style="list-style-type: none"> • Product Line Information Related Products: <ul style="list-style-type: none"> • Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: <ul style="list-style-type: none"> • Product Type = Fixed Resistor • Resistor Type = General Purpose Resistor • Resistance (Ω) = 100K • Element = Carbon Film • Termination Type = Tinned Copper Leads Electrical Characteristics: <ul style="list-style-type: none"> • Resistance Selection (Ω) = K • Power Rating (W) = 0.25 • Tolerance (%) = 5 • Package Type = Ammo Packed Body Related Features: <ul style="list-style-type: none"> • Series = CFR16 • Mount Style = Axial Leaded • Package, Component Size = 3.4 x 1.8 	Industry Standards: <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C • RoHS/ELV Compliance History = Converted to comply with RoHS directive Conditions for Usage: <ul style="list-style-type: none"> • Temperature Coefficient (ppm/°C) = -1200 to 0 Operation/Application: <ul style="list-style-type: none"> • Application = Various Other: <ul style="list-style-type: none"> • Brand = Neohm