

## FCA-125-3 Product Details

	e Mid-Range Relays
Not EU RoHS or ELV Co	ompliant
Product Highlights:	
FCA 10-25 Amp Rela     DC Actuating System	
Coil Voltage = 28 VE	DC
FCA-125-3 • Contact Arrangemen • Current Rating = 25	nt = 1 Form C, SPDT, 1 C/O
View all Features	
E Internal Number: 3-161//48-	
4 Active	
V Active	
Documentation & Additional Information	
Product Drawings:         • None Available	Additional Information: <ul> <li>Product Line Information</li> </ul>
Catalog Pages/Data Sheets:	Related Products:
• <u>RELAY</u> (PDF, English)	• <u>Tooling</u>
Product Specifications:	
None Available	
Application Specifications:	
None Available	
Instruction Sheets: • None Available	
None Available	
CAD Files:	
None Available	
	List all Documents
Product Features (Please use the Product Drawing	g for all design activity)
Product Type Features:	Configuration Related Features:
Product Features (Please use the Product Drawing Product Type Features: • <u>Terminal Configuration</u> = Solder Hook	Configuration Related Features: • <u>Contact Arrangement</u> = 1 Form C, SPDT, 1 C/O
Product Type Features: • <u>Terminal Configuration</u> = Solder Hook	Configuration Related Features: • <u>Contact Arrangement</u> = 1 Form C, SPDT, 1 C/O • <u>Coil Suppression Diode</u> = Without
Product Type Features: • <u>Terminal Configuration</u> = Solder Hook	Configuration Related Features: • <u>Contact Arrangement</u> = 1 Form C, SPDT, 1 C/O
Product Type Features: • Terminal Configuration = Solder Hook Electrical Characteristics:	Configuration Related Features: • <u>Contact Arrangement</u> = 1 Form C, SPDT, 1 C/O • <u>Coil Suppression Diode</u> = Without • Coil Magnetic System = Polarized, Monostable
Product Type Features: • Terminal Configuration = Solder Hook Electrical Characteristics: • Actuating System = DC	Configuration Related Features: • <u>Contact Arrangement</u> = 1 Form C, SPDT, 1 C/O • <u>Coil Suppression Diode</u> = Without
Product Type Features: • Terminal Configuration = Solder Hook Electrical Characteristics: • Actuating System = DC • Coil Voltage (VDC) = 28 • Current Rating (A) = 25	Configuration Related Features: Contact Arrangement = 1 Form C, SPDT, 1 C/O Coil Suppression Diode = Without Coil Magnetic System = Polarized, Monostable Industry Standards: Government/Industry Qualification = Yes Government/Industry Part Number = M6106/19-003
Product Type Features: • Terminal Configuration = Solder Hook Electrical Characteristics: • Actuating System = DC • Coil Voltage (VDC) = 28 • Current Rating (A) = 25 Termination Related Features:	Configuration Related Features: Contact Arrangement = 1 Form C, SPDT, 1 C/O Coil Suppression Diode = Without Coil Magnetic System = Polarized, Monostable Industry Standards: Government/Industry Qualification = Yes Government/Industry Part Number = M6106/19-003 RoHS/ELV Compliance = Not ELV/RoHS compliant
Product Type Features: • Terminal Configuration = Solder Hook Electrical Characteristics: • Actuating System = DC • Coil Voltage (VDC) = 28 • Current Rating (A) = 25 Termination Related Features: • Terminal Plating = Tin-Lead	Configuration Related Features: Contact Arrangement = 1 Form C, SPDT, 1 C/O Coil Suppression Diode = Without Coil Magnetic System = Polarized, Monostable Industry Standards: Government/Industry Qualification = Yes Government/Industry Part Number = M6106/19-003 RoHS/ELV Compliance = Not ELV/RoHS compliant Lead Free Solder Processes = Not suitable for lead free
Product Type Features: • Terminal Configuration = Solder Hook Electrical Characteristics: • Actuating System = DC • Coil Voltage (VDC) = 28 • Current Rating (A) = 25 Termination Related Features:	Configuration Related Features: Contact Arrangement = 1 Form C, SPDT, 1 C/O Coil Suppression Diode = Without Coil Magnetic System = Polarized, Monostable Industry Standards: Government/Industry Qualification = Yes Government/Industry Part Number = M6106/19-003 RoHS/ELV Compliance = Not ELV/RoHS compliant
Product Type Features: • Terminal Configuration = Solder Hook Electrical Characteristics: • Actuating System = DC • Coil Voltage (VDC) = 28 • Current Rating (A) = 25 Termination Related Features: • Terminal Plating = Tin-Lead	Configuration Related Features: Contact Arrangement = 1 Form C, SPDT, 1 C/O Coil Suppression Diode = Without Coil Magnetic System = Polarized, Monostable Industry Standards: Government/Industry Qualification = Yes Government/Industry Part Number = M6106/19-003 RoHS/ELV Compliance = Not ELV/RoHS compliant Lead Free Solder Processes = Not suitable for lead free
Product Type Features: • Terminal Configuration = Solder Hook Electrical Characteristics: • Actuating System = DC • Coil Voltage (VDC) = 28 • Current Rating (A) = 25 Termination Related Features: • Terminal Plating = Tin-Lead • Auxiliary Contacts = Without	Configuration Related Features: Contact Arrangement = 1 Form C, SPDT, 1 C/O Coil Suppression Diode = Without Coil Magnetic System = Polarized, Monostable Industry Standards: Government/Industry Qualification = Yes Government/Industry Part Number = M6106/19-003 ROHS/ELV Compliance = Not ELV/RoHS compliant Lead Free Solder Processes = Not suitable for lead free processing