


FCA-410-1522M Product Details



FCA-410-1522M

Military/Aerospace Mid-Range Relays

Not EU RoHS or ELV Compliant

Product Highlights:

- FCA 10-25 Amp Relay Series

- DC Actuating System
 Coil Voltage = 28 VDC
 Contact Arrangement = 4 Form C, 4PDT, 4 C/O
 Current Rating = 10 A

View all Features



Documentation & Additional Information Product Drawings: • MSD RELAY (PDF, English) Additional Information: Catalog Pages/Data Sheets: Related Products: Tooling Product Specifications: Application Specifications: Instruction Sheets: • None Available CAD Files: • None Available

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

nal Configuration = Socket Pins

Electrical Characteristics:

- <u>Actuating System</u> = DC
- Coil Voltage (VDC) = 28
- Current Rating (A) = 10

Termination Related Features:

- Terminal Plating = Gold
- Auxiliary Contacts = Without

Body Related Features: • Series = FCA 10-25 Amp Relay

- Mount Type = Bottom Mount

Configuration Related Features:

- Contact Arrangement = 4 Form C, 4PDT, 4 C/O
- Coil Suppression Diode = Without
- Coil Magnetic System = Polarized, Monostable

Industry Standards:

List all Documents

- Government/Industry Qualification = Yes
- Government/Industry Part Number = M83536/15-022M
- RoHS/ELV Compliance = Not ELV/RoHS compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process

Other:
• Brand = CII