

#### **Documentation & Additional Information**

### Product Drawings:

None Available

- Catalog Pages/Data Sheets:
  - ALCOSWITCH PRODUCTS (PDF, English)

#### Product Specifications:

None Available

- **Application Specifications:** 
  - None Available

# Instruction Sheets:

None Available

#### CAD Files:

• None Available

# Additional Information:

Product Line Information

**Related Products:** 

<u>Tooling</u>

#### List all Documents

Product Features (Please use the Product Drawing for all design activity)

## **Housing Related Features:**

- Remove Key = Position 1
- Soldering Type = Hand
- Cylinder Material = Zinc Alloy
- Lock Body = Zinc Alloy
- Key Changes = 25 Standard
- Life Expectancy = 10,000 Cycles

### **Configuration Related Features:**

- Operating Function = Position 1 Off, Position 2 On
- Contact Timing = Non-Shorting

#### **Industry Standards:**

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

## Other:

• Brand = Alcoswitch

## 

- Frame Material = Stainless Steel
- Configuration (Pole-Throw) = Single Pole Single Throw
- Comment = All keylocks are supplied with 2 brass keys on a ring.

#### **Electrical Characteristics:**

- Contact Resistance (m•) = 50
- Contact Rating = 1A @ 120 VAC

# **Body Related Features:**

- Series = SWK
- Actuator Travel = 90°
- Actuator Material = Brass

## **Contact Related Features:**

- Contact Finish = Silver Plate
- Terminals/Fixed Contact Type = Screw/Solder