

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Relays</u> > <u>Product Feature Selector</u> > Product Details

## **IACM-5** Product Details

	Solid State Relays and Input/Output Modules
A state of the sta	Converted to EU RoHS/ELV Compliant (Statement of Compliance)
	<ul> <li>Product Highlights:</li> <li>Input/Output Module</li> <li>Relay Type = Solid State Input/Output Module</li> </ul>
IACM-5	<ul> <li>IACM Series</li> <li>Switch Arrangement = 1 Form A (SPST-NO)</li> <li>Current Rating = 0.05 Amps.</li> </ul>
Active	View all Features

<ul> <li>None Available</li> <li>CAD Files: (CAD Format &amp; Compression Information) <ul> <li>2D Drawing (DXF, Version B)</li> <li>3D Model (IGES, Version B)</li> <li>3D Model (STEP, Version B)</li> </ul> </li> <li>List all Documents</li> </ul>	
--	--

• Switch Arrangement = 1 Form A (SPST-NO)

Approx. Dimensions (L x W x H) (mm [in]) = 43.20 x

• Approved Standards = UL Recognized, CSA Certified

• <u>Lead Free Solder Processes</u> = Wave solder capable to

• RoHS/ELV Compliance History = Converted to comply

• <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV

• Output Switching = Random

• Mounting Options = Board Mount

10.20 x 25.40 [1.702 x .401 x 1.000]

240°C, Wave solder capable to 260°C

• Output Type = DC

• Coupling = Optical

with RoHS directive

• Brand = Potter & Brumfield

•

Other:

Industry Standards:

compliant

Housing Style = Slim Line
Comment = Minimum Output Current >0 A

• Termination Type = Printed Circuit Terminals

## **Electrical Characteristics:**

- Current Rating (Amps.) = 0.05
- Logic Voltage (VDC) = 5
- Input Voltage Typical (VAC [VDC]) = 120 [120]
- Output Voltage, Max. (V) = 30
- Output Current, Min. (Amps.) = 0

## **Body Related Features:**

- <u>Series</u> = IACM
- Case Color = Yellow