
CWT-3-W122-5 Product Details



CWT-3-W122-5

TE Part Number: 537543-000





Shield Terminators

Not EU RoHS or ELV Compliant

Product Highlights:

- Sealing = Splash Resistant
- Cable Temperature Rating = $85 \, ^{\circ}\text{C}$
- Jacket Outer Diameter = 2.70 mm
- Shield O.D. (Min.) = 1.80 mm
- With Preinstalled Lead

View all Features | Find Similar Products

Quick Links

- Check Pricing & Availability
- Search for Tooling
- Product Feature
- Selector

 Contact Us
- Contact Us
 About This
 Product
- Request Samples



Documentation & Additional Information

Product Drawings:

• SolderSleeve Terminator with Pre-installed Lead (PDF, English)

Catalog Pages/Data Sheets:

• Wire and Cable, Harnessing and Protection Products (PDF, English)

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

• None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Mechanical Attachment:

• Inside Diameter (mm [in]) = 2.50 [0.100]

Body Related Features:

- <u>Jacket Outer Diameter (mm [in])</u> = 2.70 [0.105]
- Preinstalled Lead Plating = Tin

Housing Related Features:

- Sealing = Splash Resistant
- Shield O.D. (Min.) (mm [in]) = 1.80 [0.070]
- Preinstalled Lead = With
- Preinstalled Lead Wire Size (mm² [AWG]) = 0.38 [22]
- MIL or NAS Specification (MIL-S-83519) (NAS 1747) = No
- Preinstalled Lead Type = XL Polyethylene
- Preinstalled Lead Stranding = Stranded
- Preinstalled Lead Color = Green
- Length (Max.) (mm [in]) = 24.50 [0.950]

Configuration Related Features:

• Temperature Indication System = Without

Industry Standards:

- RoHS/ELV Compliance = Not ELV/RoHS compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process

Conditions for Usage:

- Cable Temperature Rating (°C) = 85
- Operating Temperature (Max.) (°C) = 125

Other:

• Brand = Raychem