<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Protection Products</u> > <u>Product Feature Selector</u> > Product Details

CWT-5-W122-5 Product Details



Documentation & Additional Information

Product Drawings:

• SolderSleeve Terminator with Pre-installed Lead (PDF, English)

Catalog Pages/Data Sheets:

• Wire and Cable, Harnessing and Protection Products (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

• None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Related Products:

<u>Tooling</u>

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Mechanical Attachment:

• Inside Diameter (mm [in]) = 4.30 [0.170]

Body Related Features:

- Jacket Outer Diameter (mm [in]) = 4.50 [0.180]
- Preinstalled Lead Plating = Tin

Housing Related Features:

- <u>Sealing</u> = Splash Resistant
- <u>Shield O.D. (Min.) (mm [in])</u> = 2.30 [0.090]
- Preinstalled Lead = With
- Preinstalled Lead Wire Size (mm² [AWG]) = 0.38 [22]
- MIL or NAS Specification (MIL-S-83519) (NAS 1747) = No
- Preinstalled Lead Type = XL Polyethylene
- Preinstalled Lead Stranding = Stranded
- Preinstalled Lead Color = Green
- Length (Max.) (mm [in]) = 29.30 [1.150]

Configuration Related Features:

• Temperature Indication System = Without

Industry Standards:

- <u>RoHS/ELV Compliance</u> = Not ELV/RoHS compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process

Conditions for Usage:

- <u>Cable Temperature Rating (°C)</u> = 85
- Operating Temperature (Max.) (°C) = 125

Other:

• Brand = Raychem