

RN73C2A10KBTG Product Details

	Finad Desistans	- Oviale Links
	Fixed Resistors	Quick Links
	Converted to EU RoHS/ELV Compliant (St	atement of Check Pricing & Availability Search for Tooling
	Compliance)	Product Feature Selector
	Product Highlights:	Contact Us About This Product
	Fixed Resistor	
RN73C2A10KBTG	 Resistor Type = Precision Resistor Resistance Selection = K Ω 	
	 Resistance = 10K Ω 	
TE Internal Number: 1676153-1	 Power Rating = .10 W 	
Active	View all Features	
	Add to My Part List Request Samp	ble Find Similar Products Buy Product
	<u> </u>	<u> </u>
Documentation & Additional I	nformation	
Product Drawings:		Additional Information:
None Available		<u>Product Line Information</u>
Catalog Pages/Data Sheets:		Related Products:
High Precision Resistors (SMD) - Type RN73 Series (PDF, English)	• <u>Tooling</u>
Product Specifications: • None Available		
 Application Specifications: None Available 		
Instruction Sheets: • None Available		
CAD Files: • None Available		
		cuments
	List all Doo	
Product Features (Please use	List all Doo	
Product Type Features:	the Product Drawing for all design activity)	Standards:
Product Type Features: • Product Type = Fixed Res	the Product Drawing for all design activity) istor • Rc	HS/ELV Compliance = RoHS compliant, ELV compliant
 Product Type Features: Product Type = Fixed Res Resistor Type = Precision 	the Product Drawing for all design activity) istor Resistor Legonation (Control of the second secon	HS/ELV Compliance = RoHS compliant, ELV compliant
Product Type Features: • Product Type = Fixed Res • Resistor Type = Precision • Resistance (Ω) • 10K	the Product Drawing for all design activity) istor Resistor Resistor	<u>HS/ELV Compliance</u> = RoHS compliant, ELV compliant <u>ad Free Solder Processes</u> = Reflow solder capable to 245°C, flow solder capable to 260°C HS/ELV Compliance History = Converted to comply with
 Product Type Features: Product Type = Fixed Res Resistor Type = Precision 	the Product Drawing for all design activity) istor Resistor Resistor	HS/ELV Compliance = RoHS compliant, ELV compliant ad Free Solder Processes = Reflow solder capable to 245°C, flow solder capable to 260°C
Product Type Features: • Product Type = Fixed Res • Resistor Type = Precision • Resistance (Ω) = 10K • Element = Thin Film • Termination Type = Solde	the Product Drawing for all design activity) istor Resistor er	HS/ELV Compliance = RoHS compliant, ELV compliant ad Free Solder Processes = Reflow solder capable to 245°C, eflow solder capable to 260°C HS/ELV Compliance History = Converted to comply with HS directive
Product Type Features: • Product Type = Fixed Res • Resistor Type = Precision • Resistance (Ω) = 10K • Element = Thin Film • Termination Type = Solde Electrical Characteristics:	the Product Drawing for all design activity) istor Resistor er er Conditior	<u>HS/ELV Compliance</u> = RoHS compliant, ELV compliant <u>ad Free Solder Processes</u> = Reflow solder capable to 245°C, flow solder capable to 260°C HS/ELV Compliance History = Converted to comply with
Product Type Features: • Product Type = Fixed Res • Resistor Type = Precision • Resistance (Ω) = 10K • Element = Thin Film • Termination Type = Solde Electrical Characteristics: • Resistance Selection (Ω)	the Product Drawing for all design activity) istor Resistor ar = K K Le Resistor Condition • Te	<pre>bHS/ELV Compliance = RoHS compliant, ELV compliant ad Free Solder Processes = Reflow solder capable to 245°C, flow solder capable to 260°C bHS/ELV Compliance History = Converted to comply with bHS directive hs for Usage: mperature Coefficient (ppm/°C) = ±10</pre>
Product Type Features: • Product Type = Fixed Res • Resistor Type = Precision • Resistance (Ω) = 10K • Element = Thin Film • Termination Type = Solde Electrical Characteristics:	the Product Drawing for all design activity) istor Resistor ar = K Condition • Te Operation	<pre>bHS/ELV Compliance = RoHS compliant, ELV compliant ad Free Solder Processes = Reflow solder capable to 245°C, eflow solder capable to 260°C HS/ELV Compliance History = Converted to comply with HS directive hs for Usage: imperature Coefficient (ppm/°C) = ±10 n/Application:</pre>
Product Type Features: • Product Type = Fixed Res • Resistor Type = Precision • Resistance (Ω) = 10K • Element = Thin Film • Termination Type = Solde Electrical Characteristics: • Resistance Selection (Ω) • Power Rating (W) = 0.10	the Product Drawing for all design activity) istor Resistor er = K the Product Drawing for all design activity) Industry • Rc Re • Rc Rc • Condition • Te Operation • Ag	<pre>bHS/ELV Compliance = RoHS compliant, ELV compliant ad Free Solder Processes = Reflow solder capable to 245°C, flow solder capable to 260°C bHS/ELV Compliance History = Converted to comply with bHS directive hs for Usage: mperature Coefficient (ppm/°C) = ±10</pre>
Product Type Features: Product Type = Fixed Ress Resistor Type = Precision Resistance (Ω) = 10K <u>Element</u> = Thin Film Termination Type = Solde Electrical Characteristics: Resistance Selection (Ω) Power Rating (W) = 0.10 Tolerance (%) = 0.1 Package Type = Cut Tape Body Related Features:	the Product Drawing for all design activity) istor Resistor ar = K Length Length	<pre>bHS/ELV Compliance = RoHS compliant, ELV compliant ad Free Solder Processes = Reflow solder capable to 245°C, eflow solder capable to 260°C HS/ELV Compliance History = Converted to comply with HS directive hs for Usage: imperature Coefficient (ppm/°C) = ±10 n/Application:</pre>
Product Type Features: Product Type = Fixed Ress Resistor Type = Precision Resistance (Ω) = 10K <u>Element</u> = Thin Film Termination Type = Solde Electrical Characteristics: <u>Resistance Selection (Ω)</u> <u>Power Rating (W)</u> = 0.10 <u>Tolerance (%)</u> = 0.1 <u>Package Type</u> = Cut Tape Body Related Features: <u>Series</u> = RN73	the Product Drawing for all design activity) istor Resistor er = K e Length • Legth	<pre>bHS/ELV Compliance = RoHS compliant, ELV compliant ad Free Solder Processes = Reflow solder capable to 245°C, effow solder capable to 260°C HS/ELV Compliance History = Converted to comply with bHS directive ms for Usage: mperature Coefficient (ppm/°C) = ±10 m/Application: pplication = Precision</pre>
Product Type Features: Product Type = Fixed Ress Resistor Type = Precision Resistor Type = Precision Resistor Type = Precision Resistance (Ω) = 10K Element = Thin Film Termination Type = Solde Electrical Characteristics: Resistance Selection (Ω) Power Rating (W) = 0.10 Tolerance (%) = 0.1 Package Type = Cut Tape Body Related Features: Series = RN73 Mount Style = Surface Mod	the Product Drawing for all design activity) istor Resistor er = K e Length • Legth	<pre>bHS/ELV Compliance = RoHS compliant, ELV compliant ad Free Solder Processes = Reflow solder capable to 245°C, effow solder capable to 260°C HS/ELV Compliance History = Converted to comply with bHS directive ms for Usage: mperature Coefficient (ppm/°C) = ±10 m/Application: pplication = Precision</pre>
Product Type Features: • Product Type = Fixed Ress • Resistor Type = Precision • Resistance (Ω) = 10K • Element = Thin Film • Termination Type = Solde Electrical Characteristics: • Resistance Selection (Ω) • Power Rating (W) = 0.10 • Tolerance $(\%)$ = 0.1 • Package Type = Cut Tape Body Related Features: • Series = RN73	the Product Drawing for all design activity) istor Resistor er = K e Length ount	<pre>bHS/ELV Compliance = RoHS compliant, ELV compliant ad Free Solder Processes = Reflow solder capable to 245°C, effow solder capable to 260°C HS/ELV Compliance History = Converted to comply with bHS directive ms for Usage: mperature Coefficient (ppm/°C) = ±10 m/Application: pplication = Precision</pre>

