## <u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Circuit Breakers</u> > <u>Product Feature Selector</u> > Product Details

## W58-XB1A4A-12 Product Details



Documentation & Additional Information		
Product Drawings: • None Available		Additional Information: <ul> <li>Product Line Information</li> </ul>
Catalog Pages/Data Sheets: • <u>W58 Push To Reset Only Thermal Circuit Breaker</u> (PDF, English)		Related Products: • Tooling
Product Specifications: • None Available		
Application Specifications: <ul> <li>None Available</li> </ul>		
Instruction Sheets: • None Available		
CAD Files: • None Available		
	List all Documents	

Product Features (Please use the Product Drawing for all design activity)		
<ul> <li>Product Type Features: <ul> <li>Actuator Style = Push to Reset</li> <li>Button Color = White with Red Rate Marking, Red Trip Band</li> <li>Termination Type = 6.35 [.250] Straight Quick Connect Tab</li> </ul> </li> <li>Electrical Characteristics: <ul> <li>Current Rating (Amps.) = 12</li> <li>Operating Voltage, Max. = 50 VDC, 250 VAC</li> </ul> </li> <li>Body Related Features: <ul> <li>Series = W58</li> </ul> </li> <li>Contact Related Features: <ul> <li>Number of Poles = 1</li> <li>Trip Time at 200% = 6 to 30 Seconds</li> <li>Interrupt Capacity = 2,000 A @ 50 VDC or 1,000 A @ 250 VAC</li> </ul> </li> <li>Mounting Options = Knurled Nut/Hex Nut</li> <li>Mounting Bushing = 7/16" x .500" [12.70 mm] Long</li> <li>Approved Standards = CSA Certified</li> </ul>	<ul> <li>Configuration Related Features: <ul> <li>Circuit Function = Series Trip</li> </ul> </li> <li>Industry Standards: <ul> <li>RoHS/ELV Compliance = RoHS/Not ELV Compliant</li> <li>Lead Free Solder Processes = Not relevant for lead free process</li> <li>RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives</li> </ul> </li> <li>Purchasing Information: <ul> <li>Mounting Hardware Packaging = Assembled to Bushing</li> </ul> </li> <li>Other: <ul> <li>Brand = Potter &amp; Brumfield</li> </ul> </li> </ul>	

- 1