RHEF1000 Product Details



RHEF1000

TE Part Number: D86144-000



PolySwitch Resettable Devices



Product Highlights:

- Radial Application
- Family Name = RHEF
- Radial Construction, Through Hole Construction
- IH (Room Temperature) = 10 Amps.
- IT (Room Temperature) = 18.50 Amps.

View all Features | Find Similar Products

Documentation & Additional Information

Product Drawings:

• RHEF1000 (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

• None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = File No. E74889
- CSA File No. = 78165C

Electrical Characteristics:

- IH (Room Temperature) (Amps.) = 10
- IT (Room Temperature) (Amps.) = 18.50
- <u>Vmax Operating (V)</u> = 16
- Rmin(•) = 0.0062
- Rmax (•) = 0.0103
- R1 Max [Post Trip] (•) = 0.015
- <u>UL Rated Current (Amps.)</u> = 100
- Tripped Power Dissipation (Typical) (W) = 5.30

Termination Related Features:

• Construction = Radial, Through Hole

Body Related Features:

• Lead Type = Bottle Kink

Contact Related Features:

• Family Name = RHEF

Configuration Related Features:

• Coating = Coated

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041432

Conditions for Usage:

• Operating Temperature (Max.) (°C) = 125

Operation/Application:

• Application = Radial

Packaging Related Features:

• Packaging Method = Tape & Reel

Other:

• Brand = Raychem