



Monolithic N-Channel JFET Duals

SST404NL
SST406NL

U401NL
U404NL

U406NL

PRODUCT SUMMARY					
Part Number	$V_{GS(off)}$ (V)	$V_{(BR)GSS}$ Min (V)	g_{fs} Min (mS)	I_G Typ (pA)	$ V_{GS1} - V_{GS2} $ Max (mV)
U401NL	-0.5 to -2.5	-40	1	-2	5
SST/U404NL	-0.5 to -2.5	-40	1	-2	15
SST/U406NL	-0.5 to -2.5	-40	1	-2	40

FEATURES

- Anti Latchup Capability
- Monolithic Design
- High Slew Rate
- Low Offset/Drift Voltage
- Low Gate Leakage: 2 pA
- Low Noise
- High CMRR: 102 dB

BENEFITS

- External Substrate Bias—Avoids Latchup
- Tight Differential Match vs. Current
- Improved Op Amp Speed, Settling Time Accuracy
- Minimum Input Error/Trimming Requirement
- Insignificant Signal Loss/Error Voltage
- High System Sensitivity
- Minimum Error with Large Input Signal

APPLICATIONS

- Wideband Differential Amps
- High-Speed, Temp-Compensated, Single-Ended Input Amps
- High-Speed Comparators
- Impedance Converters


DESCRIPTION

The SST/U401NL series of high-performance monolithic dual JFETs features extremely low noise, tight offset voltage and low drift over temperature specifications, and is targeted for use in a wide range of precision instrumentation applications. This series has a wide selection of offset and drift specifications with the U401NL featuring a 5-mV offset and 10- μ V/ $^{\circ}$ C drift.

Pins 4 and 8 of the SST series, and pin 4 of the U series part

numbers enable the substrate to be connected to a positive polarity, external bias (V_{DD}) to avoid latchup.


The U series, hermetically sealed TO-78 package is available with full military processing. The SST series SO-8 package provides ease of manufacturing, and the symmetrical pinout prevents improper orientation. The SO-8 package is available with tape-and-reel options for compatibility with automatic assembly methods.



Top View

Marking Codes:

SST404NL - 404NL
SST406NL - 406NL



Top View

U401NL
U404NL
U406NL

ABSOLUTE MAXIMUM RATINGS

Gate-Drain, Gate-Source Voltage -40 V
 Gate Current 10 mA
 Lead Temperature ($1/16$ " from case for 10 sec.) 300 $^{\circ}$ C
 Storage Temperature : U Prefix -65 to 200 $^{\circ}$ C
 SST Prefix -55 to 150 $^{\circ}$ C
 For applications information see AN106.

Operating Junction Temperature -55 to 150 $^{\circ}$ C
 Power Dissipation : Per Side^a 300 mW
 Total^b 500 mW

Notes

- a. Derate 2.4 mW/ $^{\circ}$ C above 25 $^{\circ}$ C
- b. Derate 4 mW/ $^{\circ}$ C above 25 $^{\circ}$ C

SPECIFICATIONS (T _A = 25°C UNLESS OTHERWISE NOTED)										
Parameter	Symbol	Test Conditions	Typ ^a	Limits						Unit
				U401NL		SST/U404NL		SST/U406NL		
				Min	Max	Min	Max	Min	Max	
Static										
Gate-Source Breakdown Voltage	V _{(BR)GSS}	I _G = -1 μA, V _{DS} = 0 V	-58	-40		-40		-40		V
	V _{(BR)G1 - G2}	I _G = ±1 μA, V _{DS} = 0 V, V _{GS} = 0 V	±45	±30		±30		±30		
Gate-Source Cutoff Voltage	V _{GS(off)}	V _{DS} = 15 V, I _D = 1 nA	-1.5	-0.5	-2.5	-0.5	-2.5	-0.5	-2.5	
Saturation Drain Current ^b	I _{DSS}	V _{DS} = 10 V, V _{GS} = 0 V	3.5	0.5	10	0.5	10	0.5	10	mA
Gate Reverse Current	I _{GSS}	V _{GS} = -30 V, V _{DS} = 0 V	-2		-25		-25		-25	pA
		T _A = 125°C	-1							nA
Gate Operating Current	I _G	V _{DG} = 15 V, I _D = 200 μA	-2		-15		-15		-15	pA
		T _A = 125°C	-0.8		-10		-10		-10	nA
Drain-Source On-Resistance	r _{DS(on)}	V _{GS} = 0 V, I _D = 0.1 mA	250							Ω
Gate-Source Voltage	V _{GS}	V _{DG} = 15 V, I _D = 200 μA	-1		-2.3		-2.3		-2.3	V
Gate-Source Forward Voltage	V _{GS(F)}	I _G = 1 mA, V _{DS} = 0 V	0.7							
Dynamic										
Common-Source Forward Transconductance	g _{fs}	V _{DS} = 15 V, I _D = 200 μA f = 1 kHz	1.5	1	2	1	2	1	2	mS
Common-Source Output Conductance	g _{os}		1.3		2		2		2	μS
Common-Source Forward Transconductance	g _{fs}	V _{DS} = 10 V, V _{GS} = 0 V f = 1 kHz	4	2	7	2	7	2	7	mS
Common-Source Output Conductance	g _{os}		5		30		30		30	μS
Common-Source Input Capacitance	C _{iss}	V _{DS} = 15 V, I _D = 200 μA f = 1 MHz	4		8		8		8	pF
Common-Source Reverse Transfer Capacitance	C _{rss}		1.5		3		3		3	
Equivalent Input Noise Voltage	e _n	V _{DS} = 15 V, I _D = 200 μA f = 10 Hz (U Only)	10		20		20		20	nV/ √Hz
Matching										
Differential Gate-Source Voltage	V _{GS1} - V _{GS2}	V _{DG} = 10 V, I _D = 200 μA			5		15		40	mV
Gate-Source Voltage Differential Change with Temperature	$\frac{\Delta V_{GS1} - V_{GS2} }{\Delta T}$	V _{DG} = 10 V I _D = 200 μA T _A = -55 to 125°C	SST404NL	20						μV/°C
			SST406NL	40						
			All U		10		25		80	
Common Mode Rejection Ratio	CMRR	V _{DG} = 10 to 20 V, I _D = 200 μA	102	95		95				dB

Notes


- a. Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing.
 b. Pulse test: PW ≤ 300 μs duty cycle ≤ 3%.

NNR




TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)


Drain Current and Transconductance vs. Gate-Source Cutoff Voltage




Gate Leakage Current




Output Characteristics




Output Characteristics



Output Characteristics









Output Characteristics






TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)






TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)


Common-Source Input Capacitance vs. Gate-Source Voltage




Common-Source Reverse Feedback Capacitance vs. Gate-Source Voltage




Output Conductance vs. Drain Current




Equivalent Input Noise Voltage vs. Frequency



Common-Source Forward Transconductance vs. Drain Current



On-Resistance and Output Conductance vs. Gate-Source Cutoff Voltage





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.