

Identification

TECHNICAL DATA SHEET

Tyco Electronics T208M Thermal Transfer Printer

DESCRIPTION:	Small, lightweight, portable, computer-driven 200dpi thermal transfer printer. Ideal for low volume users. Specially developed to print a wide range of Tyco Electronics cable identification and labelling products
ORDERING INFORMATION:	T208M-PRINTER T208M-C-PRINTER (with optional cutter fitted)
RECOMMENDED SOFTWARE:	Tyco Electronics WinTotal software for Cable Identification product range Tyco Electronics PrintEasy software for labelling products
ELECTRICAL REQUIREMENTS:	Input- 100 to 240V AC, 50 - 60Hz, automatic switching Output- 20 VDC, 2.5A
PHYSICAL CHARACTERISTICS:	Width: 200mm (7.9 inches) Depth: 247mm (9.75 inches) Height: 171mm (6.8 inches) Weight: 1.4kg (3.2lb).
PRINT SPEED:	25 to 50mm/sec (1 to 2 inches/sec) recommended for most Tyco Identification products.
MEDIA SENSOR:	Fixed transmissive and reflective sensor
MAXIMUM PRINT AREA:	104mm x 279mm (4.09 x 11 inches).
MEDIA WIDTH:	25.4mm to108mm (1 to 4.25 inches)

www.tycoident.com	Document number: TTDS-011	Date: November 2004
	Issue: 3	Pages: 2
Business locations:	 N America: + 1 401 751 (France: + 33 (0) 476 099 UK: + 44 (0) 1793 52817 Singapore: + 65 (0) 4866 	696 1 (Other products)

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition Tyco Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.





Tyco Electronics T208M Thermal Transfer Printer

PRINTHEAD DENSITY:	8 dots/mm (203 dots/inch).
OPERATING TEMPERATURE RANGE:	4°C to 41°C (40°F to 105°F), 10% to 90% RH (non-condensing).
STORAGE TEMPERATURE RANGE:	-40°C to 60°C (-40°F to 140°F), 10% to 90% RH (non-condensing).
COMMUNICATIONS:	RS232C serial port, Centronics parallel port, USB 1.1
MEMORY	512KB Flash: 256KB SRAM
AGENCY APPROVALS:	UL, CSA, CE, TUV. Complies with FCC class A.
PRODUCT SUITABILITY:	See technical data sheets for individual Tyco Electronics identification products.
RIBBON RECOMMENDATIONS:	See technical data sheets for individual Tyco Electronics identification products.



www.tycoident.com

Business locations:

- N America: + 1 650 361 3860 (West Coast)
- Germany: + 49 (0) 6074 89080
- UK: + 44 (0) 1495 244000 (Labels)
- Japan: + 81 (0) 44 900 5102

Document number: TTDS-011

Issue: 3

Pages: 2

Date: November 2004

- N America: + 1 401 751 6505 (East Coast)
- France: + 33 (0) 476 099696
- UK: + 44 (0) 1793 528171 (Other products)
- Singapore: + 65 (0) 4866 151

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition Tyco Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.