

ISDN MAGNETICS

Surface Mount Common Mode Choke


TM00202

- Designed to filter high-frequency EMI noise from 1 MHz to 200 MHz
- Optimized for ISDN S/T-interface communications
- Minimum interwinding breakdown voltage of 500 Vrms


ELECTRICAL SPECIFICATIONS at 25° C

Part Number	Primary Inductance μH min	Leakage Inductance nH max	DCR Ω max	Interwinding Capacitance pF max
1793A	22.5	250.0	0.35	17

SCHEMATIC



TYPICAL IMPEDANCE vs. FREQUENCY






©2000 Bel Fuse Inc. Specifications subject to change without notice. 05.00

ISDN MAGNETICS Surface Mount Common Mode Choke

MECHANICAL

1793A



Note: Unless otherwise specified, dimensions are nominal and in inches [millimeters].

Suggested PCB Pad Layout

©2000 Bel Fuse Inc. Specifications subject to change without notice. 05.00

CORPORATE

Bel Fuse Inc.
198 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

T2-6

FAR EAST

Bel Fuse Ltd.
8F / 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com