


➤ ePanel-PM

Mobile Flatpanel SBC



powered by
Intel® Pentium® M



- Intel® Celeron® M and Pentium® M CPU (600 MHz up to 1.4 GHz)
- Low power consumption
- Prepared for wireless LAN/Internet, Bluetooth connections etc. via PC-CARD-Slot or Mini-PCI (e.g. for DVB-T)
- Low profile form factor
- Ideal suitable for warehouse management, indoor visual units, Rear-seat-video, ...
- Shortest time to market by highest integration of interfaces and features

Product Overview


Do you need an ultraflat single board computer to be mounted directly behind a flat panel? **ePanel-PM** is a complete SBC with a very low height based on low power Intel® Celeron® M or Pentium® M.

A wide range of software is available for this proven x86 platform. In addition to the very low power consumption, the high number of interfaces is remarkable. So, systems can be designed within a very short period and built with minor additional engineering efforts.

Technical Information

Processor	Intel® Celeron® M and Pentium® M 600 MHz - 1.4 GHz
Chipset	GM 852 or GME 855/ICH4
Memory	1 x DDR-SODIMM SDRAM, 200pin, 2.5V, up to 1GByte
Graphics	Intel® Extreme Graphics with shared memory Flatpanel Interface: TTL and LVDS on board NTSC/Pal video input Touch screen: 4/5/8 wire supported matrix controller
Ethernet	100 MBit Ethernet
USB	3 x USB 2.0

Dimensions	140 x 180 mm
Battery	Smart-Battery backup supported
Power Supply	Wide range DC (8 to 28 V)
I/O Features	Flexible I/O adapter solution: 1 x VGA / Sound connector 1 x Floppy Connector 1 x secondary IDE 1 x secondary port connector 1 x Compact Flash socket PC-CARD interface on Board Mini PCI for Bluetooth, Wireless LAN, CAN, DVB-T, etc.



Ordering Information

Article	Part.-No.	Description
ePanel-CM 600 (800) MHz	22242	ePanel-CM 600 MHz with Intel® Celeron® M ULV CPU and GM852 Chipset
ePanel-CM 1 GHz	22243	ePanel-CM 1 GHz with Intel® Celeron® M ULV CPU and GME855 Chipset
ePanel-PM 1.4 GHz	22244	ePanel-PM 1.4 GHz with Intel® Pentium® M LV CPU and GME855 Chipset
I/O Adapter	22223	I/O Adapter for standard interfaces (e.g. USB, VGA, RS232 etc.)
ePanel-PM Starterkit	60900	Including I/O-adapter, video-adapter, power supply, 512 MB CF-Card, 256 MB DDR-RAM and cables for: power supply, I2C-Bus, touch-panel and matrix keyboard, HD-Adapter. Reset-Button, Power-Button.
DDR-SDRAM-SODIMM 256 MB	97007-2560-00-0	DDR-SDRAM SODIMM PC2700 memory module with 256 MB
DDR-SDRAM-SODIMM 512MB	97007-5120-00-0	DDR-SDRAM SODIMM PC2700 memory module with 512 MB
DDR-SDRAM-SODIMM 1GB	97007-1024-00-0	DDR-SDRAM SODIMM PC2700 memory module with 1 GB

Corporate Offices

Europe, Middle East & Africa
Oskar-von-Miller-Str. 1
85386 Eching/Munich
Germany
Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 219
sales@kontron.com

North America
14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
sales@us.kontron.com

Asia Pacific
17 Building,Block #1,ABP.
188 Southern West 4th Ring Road
Beijing 100070,P.R.China
Tel.: + 86 10 63751188
Fax: + 86 10 83682438
kcn@kontron.cn

Kontron Embedded Modules GmbH
Flatpanel Solutions
Hamburger Straße 181
22083 Hamburg - Germany
Tel.: +49(40)200090-0
Fax: +49(40)200090-10
sales-graphic@kontron.com

#ePanel-PM# -20102008PDL
 All data is for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this datasheet has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies. All brand or product names are trademarks or registered trademarks of their respective owners. DIMM-PC and JUMPEC are registered trademarks of Kontron Embedded Modules GmbH, Germany.