

TR250 - 120T - 2 Product Details



TR250 - 120T - 2

TE Part Number: F53287 - 000

Obsolete

- [Add to Part List](#)
- [Contact Product Information Center](#)

PolySwitch Resettable Devices

[Always ELV Compliant](#) ([Find RoHS Compliant Alternates / Statement of Compliance](#))

Product Highlights:

- ? Telecom Application
- ? Family Name = TR250
- ? Through Hole Construction
- ? IH (Room Temperature) = .12 Amps.
- ? IT (Room Temperature) = .24 Amps.

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? None Available

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? UL Recognized = File No. E74889
- ? CSA File No. = 78165C
- ? Comment = Devices are available with 0.5 ohm resistance matching.; Designed for equipment needing to meet ITU K.20, K.21, K.45 recommendations.

Electrical Characteristics:

- ? [IH \(Room Temperature\) \(Amps.\)](#) = 0.12
- ? [IT \(Room Temperature\) \(Amps.\)](#) = 0.24
- ? [Vmax Operating \(V\)](#) = 60
- ? [Rmin \(?\)](#) = 7.00
- ? [Rmax \(?\)](#) = 12.000
- ? [R1 Max \[Post Trip\] \(?\)](#) = 16.00
- ? [Vmax Interrupt \(V rms\)](#) = 250
- ? [UL Rated Current \(Amps.\)](#) = 3
- ? Tripped Power Dissipation (Typical) (W) = 1.00
- ? R (Typical) (?) = 9.50
- ? UL Rated Voltage (V) = 60

Termination Related Features:

- ? Construction = Through Hole

Body Related Features:

- ? Lead Type = Kinked

Contact Related Features:

- ? Family Name = TR250

Configuration Related Features:

- ? Coating = Coated

Industry Standards:

- ? [RoHS/ELV Compliance](#) = ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was ELV compliant
- ? TUV Certificate No. = R72041425

Conditions for Usage:

- ? [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- ? Application = Telecom

Packaging Related Features:

- ? Packaging Method = Bulk, Tape & Reel

Other:

- ? Brand = Raychem