

164164-1

TE Internal Number: 164164-1



# **Multimate**



Always EU RoHS/ELV Compliant (Statement of

Compliance)

# **Product Highlights:**

- Pin
- Tin Contact Mating Area Plating Material
- Wire Range = 0.80-1.40<sup>2</sup> [18-16] mm [AWG]
- Insulation Diameter = 2.01 2.49 mm
- Copper Alloy Contact Base Material

View all Features

### **Documentation & Additional Information**

## **Product Drawings:**

• loose piece pin type 3+ contact size 16 (PDF, English)

## Catalog Pages/Data Sheets:

- PRECISION PIN AND SOCKET CONTACTS (PDF, English)
- Signal Contacts (PDF, English)
- M\_SERIES\_PIN\_AND\_SOCKET\_CONNECTORS (PDF, English)
- <u>CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER ...</u> (PDF, English)
- AMP Circular Connectors for Commercial Signal & Powe... (PDF, English)

# **Product Specifications:**

None Available

# **Application Specifications:**

None Available

### **Instruction Sheets:**

None Available

## **CAD Files:**

None Available

### Additional Information:

Product Line Information

### **Related Products:**

Tooling

<u>List all Documents</u>

# Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

- Pin/Socket = Pin
- <u>Insulation Diameter (mm [in])</u> = 2.01 2.49
  [0.079 0.098]
- Product Type = Type III+
- Insulation Support = Yes
- Wire Termination Type = Crimp
- Wire/Cable Type = Regular Wire
- Grade = Commercial
- Make First / Break Last = Yes
- Comment = Leading Pin (1.8mm longer than standard pins); Overall insulation crimp diameter, including crimp barrel, must not exceed 3.18 [.125].

### **Electrical Characteristics:**

High Current = No

### **Termination Related Features:**

- <u>Termination End Plating</u> = Tin
- Pin Diameter (mm [in]) = 1.57 [0.062]

### **Body Related Features:**

## **Contact Related Features:**

- Contact Mating Area Plating Material = Tin
- Contact Base Material = Copper Alloy
- Contact Size = 16
- Contact Type = Grounding

#### **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

## Conditions for Usage:

- <u>Terminate To</u> = Wire
- Test Current (Amps.) = 13.0

## **Packaging Related Features:**

- Packaging Method = Loose Piece
- Packaging Quantity = 200

### Other:

• Brand = AMP

- Wire Range (mm [AWG]) = 0.80-1.40<sup>2</sup> [18-16]
- Spring Material = Stainless Steel
- Used With = CPC Connectors