

166722-1

TE Internal Number: 166722-1

Active

Contacts-AMPMODU Machine Applied

Always EU RoHS/ELV Compliant (Statement of Always EU ROHS) (Statement

Compliance)

Product Highlights:

- Socket
- Contact Type = MTE (IDC)
- Wire Range = 0.12-0.40² [26-22] mm [AWG]
- Wire Insulation Diameter = .91 1.37 mm
- Standard Applied Pressure

View all Features

Documentation & Additional Information	
 Product Drawings: tandem spring receptacle loose piece 24-20 awg (PDF, English) 	Additional Information: • Product Line Information
Catalog Pages/Data Sheets: • None Available	Related Products: • <u>Tooling</u>
 Product Specifications: <u>Receptacle, Tandem Spring Contact</u> (PDF, English) 	
Application Specifications: • None Available	
Instruction Sheets: • None Available	
CAD Files: • None Available	
List all Documents	

Product Features (Please use the Product Drawing for all design activity)		
 Product Type Features: Pin/Socket = Socket Wire Insulation Diameter (mm [in]) = 0.91 – 1.37 [0.035 – 0.054] Applied Pressure = Standard Wire Termination Type = Crimp Termination Related Features: Solder Tail Contact Plating = Tin-Lead Body Related Features: Wire Range (mm [AWG]) = 0.12-0.40² [26-22] Contact Related Features: Contact Type = MTE (IDC) Contact Base Material = Copper Alloy Contact Mating Area Plating Material = Gold (30) 	 Industry Standards: RoHS/ELV Compliance = RoHS compliant, ELV compliant Lead Free Solder Processes = Not relevant for lead free process RoHS/ELV Compliance History = Always was RoHS compliant Packaging Related Features: Packaging Method = Loose Piece Other: Brand = AMP 	