

TRM 5015 S EN

This item is no longer available. Should you have any questions, please contact our Sales Team.

Order No.: 2875657



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2875657>

Terminal-PC with touch screen, 15" display, enclosed housing,
Windows 2000 EN

Commercial data

EAN	4017918957049
Pack	1 pcs.
Customs tariff	85371091
Weight/Piece	13.14 KG
Catalog page information	Page 411 (NTK-2004)

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Product description

The TRM 5015 S is a powerful terminal PC with touch screen and front USB, mounted in a sturdy aluminum cast housing. The cast aluminum housing (IP65) is mounted at the top using a bracket flange connection. Waste heat from the processor is dissipated into the surrounding atmosphere via the back panel of the terminal. This panel is designed as a cooling unit. The terminals are supplied with a software keyboard as standard. All the alphanumeric keys on a standard keyboard are available on the software keyboard. It is also possible to switch over to a separate numeric keypad.

Technical data

Module

Processor	800 MHz VIA C3
Main memory	256 MB SDRAM
Operating systems	Windows 2000 EN
Display	15" TFT active

Display lighting	Max. 330 cd/m ² typical (adjustable)
Touch screen	Resistive industrial touch screen
Data memory	2.5", min. 30 GB (UDMA)
Power supply unit	100 ... 240 V AC, 50/60 Hz
Optical drive	No CD-ROM
Interfaces	COM 1, COM 2, COM 3 (RS-232), 1x LPT, 1x VGA, 1x PS/2 mouse, 1x PS/2 keyboard, 2x USB (1x USB on front panel)
Disk drive	Connection for external floppy disk drive
Network	2x Ethernet (10/100 Mbit), RJ45
Keys	5 additional keys (software keyboard, change task Alt+Tab, right mouse button, brightness, user-specific function)
System architecture	Slot CPU (half-size SBC), Intel-compatible
Software keyboard	English
Monitoring	Temperature, fan rotational speed, display LEDs and via software
Graphics card	On-board graphics chip (AGP)
Monitor resolution	1024 x 768

General data

Width	451 mm
Height	325 mm
Depth	125 mm
Fixing	Support bracket joint, can be swung round from above (enclosure coupling)
Degree of protection	IP65
Ambient temperature (operation)	5 °C ... 40 °C
Ambient temperature (storage/transport)	-20 °C ... 60 °C
Permissible humidity (operation)	10 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 85 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-29

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2009 Phoenix Contact
Technical modifications reserved;