

66259-2

TE Internal Number: 66259-2

Active

## **Multimate**



# **Product Highlights:**

- Pin
- Gold (30) over Nickel (30) Contact Mating Area Plating Material
- Wire Range = 5.00-8.00<sup>2</sup> [10-8] mm [AWG]
- Insulation Diameter = 4.83 5.59 mm
- Copper Contact Base Material

View all Features

### **Documentation & Additional Information**

#### **Product Drawings:**

• MALE TYPE XII CONTACT LOOSE PIECE ASSY (PDF, English)

### Catalog Pages/Data Sheets:

- PRECISION PIN AND SOCKET CONTACTS (PDF, English)
- Power Contacts (PDF, English)
- M\_SERIES\_PIN\_AND\_SOCKET\_CONNECTORS (PDF, English)
- <u>CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER ...</u> (PDF, English)
- AMP Circular Connectors for Commercial Signal & Powe... (PDF, English)

### **Product Specifications:**

- <u>Circular Plastic Connector With Type XII Contacts</u> (PDF, English)
- Contact, Type XII (PDF, English)

## **Application Specifications:**

• Type XII Contacts (PDF, English)

#### Instruction Sheets:

 AMP\* EXTRACTION TOOL (CATALOG NO. 91019-3) FOR AMP T... (PDF, English)

### **CAD Files:** (CAD Format & Compression Information)

- 2D Drawing (DXF, Version Z)
- 3D Model (IGES, Version Z)
- 3D Model (STEP, Version Z)

List all Documents

### **Additional Information:**

Product Line Information

#### **Related Products:**

Tooling

### Product Features (Please use the Product Drawing for all design activity)

### **Product Type Features:**

- <u>Pin/Socket</u> = Pin
- <u>Insulation Diameter (mm [in])</u> = 4.83 5.59
   [0.190 0.220]
- Product Type = Type XII
- Insulation Support = Yes
- <u>Wire Termination Type</u> = Crimp
- Wire/Cable Type = Discrete Wire
- Grade = Commercial
- Comment = Hand Tool No. 69710-1 uses Die Insert No. 90145-2 for 16 AWG and Die Insert No. 90145-1 for 14-12 AWG wire.

## **Electrical Characteristics:**

• High Current = No

#### **Termination Related Features:**

#### **Contact Related Features:**

- <u>Contact Mating Area Plating Material</u> = Gold
   (30) over Nickel (30)
- Contact Base Material = Copper
- Contact Size = Power Contact
- Contact Type = Power

#### **Industry Standards:**

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Conditions for Usage:

• Terminate To = Wire

• Termination End Plating = Gold (30)

## **Body Related Features:**

- Wire Range (mm [AWG]) = 5.00-8.00<sup>2</sup> [10-8]
- Used With = G Series Connectors, M Series Connectors, CPC Connectors

• Test Current (Amps.) = 35.0

## **Packaging Related Features:**

• <u>Packaging Method</u> = Loose Piece

#### Other:

• Brand = AMP