
66259-4 Product Details



66259-4

TE Internal Number: 66259-4



Multimate



Always EU RoHS/ELV Compliant (Statement of

Compliance)

Product Highlights:

- Pin
- Silver Contact Mating Area Plating Material
- Wire Range = 5.00-8.00² [10-8] mm [AWG]
- Insulation Diameter = 4.83 5.59 mm
- Copper Contact Base Material

View all Features

Documentation & Additional Information

Product Drawings:

• MALE TYPE XII CONTACT LOOSE PIECE ASSY (PDF, English)

Catalog Pages/Data Sheets:

- PRECISION PIN AND SOCKET CONTACTS (PDF, English)
- Power Contacts (PDF, English)
- M_SERIES_PIN_AND_SOCKET_CONNECTORS (PDF, English)
- <u>CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER ...</u> (PDF, English)
- AMP Circular Connectors for Commercial Signal & Powe... (PDF, English)

Product Specifications:

Contact, Type XII (PDF, English)

Application Specifications:

• Type XII Contacts (PDF, English)

Instruction Sheets:

AMP* EXTRACTION TOOL (CATALOG NO. 91019-3) FOR AMP
 T... (PDF, English)

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version Z)
- 3D Model (IGES, Version Z)
- 3D Model (STEP, Version Z)

List all Documents

Additional Information:

Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Pin/Socket = Pin
- <u>Insulation Diameter (mm [in])</u> = 4.83 5.59
 [0.190 0.220]
- Product Type = Type XII
- Insulation Support = Yes
- Wire Termination Type = Crimp
- Wire/Cable Type = Discrete Wire
- Grade = Commercial
- Comment = Hand Tool No. 69710-1 uses Die Insert No. 90145-2 for 16 AWG and Die Insert No. 90145-1 for 14-12 AWG wire.

Electrical Characteristics:

• High Current = No

Termination Related Features:

• <u>Termination End Plating</u> = Silver

Contact Related Features:

- Contact Mating Area Plating Material = Silver
- Contact Base Material = Copper
- Contact Size = Power Contact
- Contact Type = Power

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Terminate To = Wire
- Test Current (Amps.) = 35.0

Packaging Related Features:

Body Related Features:

- Wire Range (mm [AWG]) = 5.00-8.00² [10-8]
- Used With = G Series Connectors, M Series Connectors, CPC Connectors

• <u>Packaging Method</u> = Loose Piece

Other:

• Brand = AMP