

66590-4

TE Internal Number: 66590-4

Active

# Multimate



# **Product Highlights:**

- Socket
- Gold (30) Contact Mating Area Plating Material
- Wire Range = 0.80-1.40<sup>2</sup> [18-16] mm [AWG]
- Insulation Diameter = 2.03 2.54 mm
- Brass Contact Base Material

View all Features

### Documentation & Additional Information

### **Product Drawings:**

• CONTACT, SOCKET, LOOSE PIECE, TYPE VI, MULTIMATE (PDF, English)

# Catalog Pages/Data Sheets:

None Available

# **Product Specifications:**

None Available

### **Application Specifications:**

• Type VI Insulation Grip Contacts (PDF, English)

# **Instruction Sheets:**

None Available

# **CAD Files:** (CAD Format & Compression Information)

- 2D Drawing (DXF, Version G)
- 3D Model (IGES, Version G)
- 3D Model (STEP, Version G)

List all Documents

### Additional Information:

• Product Line Information

#### **Related Products:**

Tooling

# Product Features (Please use the Product Drawing for all design activity)

# **Product Type Features:**

- <u>Pin/Socket</u> = Socket
- <u>Insulation Diameter (mm [in])</u> = 2.03 2.54
   [0.080 0.100]
- Product Type = Type VI
- <u>Insulation Support</u> = Yes
- <u>Wire Termination Type</u> = Crimp
- Wire/Cable Type = Discrete Wire
- Grade = Commercial
- Comment = Wire strip length-- 3.96 [.156] for all wire sizes.

#### **Electrical Characteristics:**

• High Current = No

# **Termination Related Features:**

- <u>Termination End Plating</u> = Tin
- Pin Diameter (mm [in]) = 1.57 [0.062]

# **Body Related Features:**

- Wire Range (mm [AWG]) = 0.80-1.40<sup>2</sup> [18-16]
- Spring Material = Stainless Steel
- Used With = G Series Connectors

### **Contact Related Features:**

- Contact Mating Area Plating Material = Gold (30)
- Contact Base Material = Brass
- Contact Size = 16
- Contact Type = Signal

#### **Industry Standards:**

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Conditions for Usage:

- <u>Terminate To</u> = Wire
- Test Current (Amps.) = 13.0

# **Packaging Related Features:**

• Packaging Method = Loose Piece

# Other:

• Brand = AMP