

66740-2

TE Internal Number: 66740-2



Multimate



Always EU RoHS/ELV Compliant (Statement of

Compliance)

Product Highlights:

- Socket
- Silver Contact Mating Area Plating Material
- Wire Range = 1.25-1.40² [16] mm [AWG], 2.00-3.00² [14-12] mm [AWG]
- Insulation Diameter = 3.43 4.06 mm
- Copper Contact Base Material

View all Features

Documentation & Additional Information

Product Drawings:

• FEMALE TYPE XII CONTACT ASSEMBLY, WITH ASSIST SPRING (PDF, English)

Catalog Pages/Data Sheets:

- PRECISION PIN AND SOCKET CONTACTS (PDF, English)
- Power Contacts (PDF, English)
- M_SERIES_PIN_AND_SOCKET_CONNECTORS (PDF, English)
- <u>CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER ...</u> (PDF, English)
- AMP Circular Connectors for Commercial Signal & Powe... (PDF, English)

Product Specifications:

• Contact, Type XII (PDF, English)

Application Specifications:

• Type XII Contacts (PDF, English)

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- <u>2D Drawing</u> (DXF, Version F)
- <u>3D Model</u> (IGES, Version F)
- 3D Model (STEP, Version F)

<u>List all Documents</u>

Additional Information:

Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Pin/Socket = Socket
- <u>Insulation Diameter (mm [in])</u> = 3.43 4.06
 [0.135 0.160]
- Product Type = Type XII
- Insulation Support = Yes
- Wire Termination Type = Crimp
- Wire/Cable Type = Discrete Wire
- Grade = Commercial
- Comment = Hand Tool No. 69710-1 uses Die Insert No. 90145-2 for 16 AWG and Die Insert No. 90145-1 for 14-12 AWG wire.

Electrical Characteristics:

High Current = No

Termination Related Features:

Termination End Plating = Silver

Contact Related Features:

- Contact Mating Area Plating Material = Silver
- <u>Contact Base Material</u> = Copper
- Contact Size = Power Contact
- Contact Type = Power

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Terminate To = Wire
- Test Current (Amps.) = 35.0

Packaging Related Features:

Body Related Features:

- Wire Range (mm [AWG]) = 1.25-1.40² [16], 2.00-3.00² [14-12]
- Used With = G Series Connectors, CPC Connectors, M Series Connectors

• <u>Packaging Method</u> = Loose Piece

Other:

• Brand = AMP