
6-87756-6 Product Details



6-87756-6

TE Internal Number: 6-87756-6



.100 AMPMODU Headers, Housings & Contacts



Always EU RoHS/ELV Compliant (Statement of

Compliance)

Product Highlights:

- Contact
- Contact Type = Receptacle
- Terminate To Wire
- Wire Insulation Diameter = 1.55 mm
- Wire Range = 0.12-0.40² [26-22] mm [AWG]

View all Features

Documentation & Additional Information

Product Drawings:

• CONTACT, FEMALE, MOD IV, CRIMP SNAP-IN (PDF, English)

Catalog Pages/Data Sheets:

 AMPMODU_INTERCONNECTION_SYSTEM_SECTION5_CONT (PDF, English)

Product Specifications:

 PRODUCT SPECIFICATION INTERCONNECTION SYSTEM, <u>AMPMOD...</u> (PDF, English)

Application Specifications:

 AMPMODU MOD IV, IV1/2, and V Receptacles and Housings (PDF, English)

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version T)
- 3D Model (IGES, Version T)
- 3D Model (STEP, Version T)

List all Documents

Additional Information:

Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Contact
- Wire Insulation Diameter (mm [in]) = 1.55 [0.061]
- Connector Series = Mod IV
- Wire Termination Type = Crimp
- With Insulation Support = Yes
- Applied Pressure = Standard
- Comment = (*) For use with Model "K" machines. Call the Technical Assistance Center (1-800-522-6752) for part numbers of applicators for use with Model "G" machines, as well as other bench machines and fully automatic AMPOMATOR lead making machines.

Electrical Characteristics:

- Voltage Rating (VAC) = 250
- Contact Current Rating (Amps.) = 3
- Termination Resistance (m) = 12
- Insulation Resistance (M) = 5,000
- Dielectric Withstanding Voltage (V) = 750

Termination Related Features:

Crimp Area Plating = Matte Tin

Body Related Features:

 Wire Range (mm [AWG]) = 0.12-0.40² [26-22]

Contact Related Features:

- Contact Type = Receptacle
- <u>Contact Mating Area Plating Material</u> = Gold (15)
- Contact Base Material = Copper-Tin-Phosphor Bronze
- Approved Standards = UL E28476, CSA LR7189

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Terminate To = Wire
- Operating Temperature (°C) = -65 +105

Packaging Related Features:

• Packaging Method = Loose Piece

Other:

Brand = AMP