

SEARCH

PART # DOC SITE

LCD Product Brief

SITE MAP CONTACT US PRINT

Display Overview

Product Lineup

- 3.5" Lineup
- 5.5" Lineup
- 6.3" Lineup
- 6.5" Lineup
- 7.0" Lineup
- 8.4" Lineup
- 9.0" Lineup
- 10.4" Lineup
- NL10276BC20-04
- NL10276BC20-04C
- NL10276BC20-08
- NL6448BC33-50
- NL6448BC33-53
- NL6448BC33-54
- NL6448BC33-63C
- NL6448BC33-63D
- NL6448BC33-64
- NL6448BC33-64C
- NL8060BC26-27
- NL8060BC26-28**
- NL8060BC26-30D
- 12.1" Lineup
- 15.0" Lineup
- 15.3" Lineup
- 19.0" Lineup
- 20.1" Lineup
- 21.3" Lineup
- 22.5" Lineup

10.4 inches (26 cm) SVGA for industrial applications SA-SFT

Characteristics

Model number	NL8060BC26-28
Drive method	a-Si TFT active matrix
Screen size	10.4 inches (26 cm diagonal)
Number of pixels	800 x 600
Effective display area	211.2 (H) x 158.4 (V) mm
Backlight	One side 2 CCFL
Luminance	400 cd/m2
Contrast	700:1
Display colors	16.77M colors (8bit) / 262K colors (6bit)
Viewing angle	Up: 85°, down: 85°, right: 85°, left: 85° [1]
Response time (t_{on})	50 ms [2]
Outline dimension	243.0 (W) x 185.1 (H) x 10.5 (D) mm
Weight	475 g
Operating temperature	-10°C to +70°C
Storage temperature	-20°C to +80°C
Power supply voltage	3.3 V
Power consumption	6.5 W [3]
Input signal	LVDS (RGB 8 bits each / 6 bits each)
Remark	-

FEATURE

- FF-Compatibility
- Super Fine Technology

Industrial TFT

Transflective TFT

Markets

Support

Note:
 [1] Contrast of 10:1 or higher
 [2] Value of Ton+Toff (0% ↔ 90%)
 [3] Value does not include power consumption of recommended inverter

All values are typical values.
 All specifications shown on this web site are subject to change without notice.