

SEARCH

PART # | DOC | SITE

Display Overview

Product Lineup

3.5" Lineup

5.5" Lineup

6.3" Lineup

6.5" Lineup

NL10276BC13 -01C

NL6448BC20 -18D

NL6448BC20 -20

7.0" Lineup

8.4" Lineup

9.0" Lineup

10.4" Lineup

12.1" Lineup

15.0" Lineup

15.3" Lineup

19.0" Lineup

20.1" Lineup

21.3" Lineup

Industrial TFT

Transflective TFT

Markets

Support

SITE MAP

CONTACT US

PRINT

LCD Product Brief

NL6448BC20 -20

6.5 inches (17 cm) VGA for industrial applications
ST - NLT

FEATURE

[FFF-Compatibility](#)

Characteristics

Model number	NL6448BC20 -20
Drive method	a-Si TFT active matrix
Screen size	6.5 inches (17 cm diagonal)
Number of pixels	640 x 480
Effective display area	132.48 (H) x 99.36 (V) mm
Backlight	One side 2 CCFL
Luminance	650 cd/m2
Contrast	600:1
Display colors	262k colors
Viewing angle	Up: 80°, down: 60°, right: 80°, left: 80° [1]
Response time (t_{on})	25 ms [2]
Outline dimension	153 (W) x 118.0 (H) x 10.5 (D) mm
Weight	205 g
Operating temperature	-10°C to +70°C
Storage temperature	-20°C to +80°C
Power supply voltage	3.3 V (5 V)
Power consumption	4.4 W [3]
Input signal	CMOS (RGB 6 bits each)
Remark	ST-NLT

Note:

[1] Contrast of 10:1 or higher

[2] Value of Ton+Toff (0% ? 90%)

[3] Value does not include power consumption of recommended inverter

All values are typical values.

All specifications shown on this web site are subject to change without notice.