



- NOTES:
- 1. PA66 NATURAL MATERIAL ACC TO SPEC IEC 60335-1 GWT 750° WITHOUT FLAME
 - 2. MOISTURISED PRODUCT FOR SMALL WIRE APPLICATIONS
 - 3. ONLY FOR USE WITH POST PLATED OR WASHED CONTACTS
 - 4. RIB MAY EXTEND TO FRONT OF HOUSING

| LOC | QST | REVISIONS | | | | | |
|-----|-----|-----------|---------------|-------------|--------|-----|------|
| E | B | F | LTN | DESCRIPTION | DATE | SWN | APRD |
| | | AV | ECR-10-002350 | | 090210 | MJG | JA |
| | | | | | | | |
| | | | | | | | |

| 2 | 8-154719-6 | As Drg | UL 94 V0 | 7-154719-0 | Orange |
|-------|-------------|---------------|---------------------|--|-------------------|
| 2 | 8-154719-5 | As Drg | UL 94 V2 | 154719-1 | Natural |
| 1 | 8-154719-4 | As Drg | UL 94 V0 | POLYAMIDE 6.6 V0 | Natural |
| | 8-154719-3 | As Drg. | UL 94 V0 | Ultramid C3U | Terracotta |
| 2 | 8-154719-1 | As Drg. | UL 94 V2 | 154719 | Black |
| | 8-154719-0 | As drg. | UL 94 V0 | Maranyl A.417 | Clear |
| | 7-154719-0 | AE | UL 94 V0 | Zytel 7200VOF Nat.NC010 703084-2 or Equivalent | Orange (Ral 2000) |
| | 6-154719-6 | AB | UL 94 V2 | Polyester PBT 703167 | Black |
| | 5-154719-0 | AB | UL 94 V0 | Noryl (VO 150) | Orange |
| | 4-154719-0 | AA | UL 94 V0 | Zyfel FR 10 | (Bk-59 Black) |
| 3 | 2-154719-0 | AA | UL 94 V0 | Noryl (VO 150) | Red |
| | 1-154719-1 | As Drg. | UL 94 V0 | TECHNYL B 50H1 | Natural |
| | 1-154719-0 | AE | UL 94 V0 | Ultramid KR4205 | Natural |
| | 154719-9 | As Drg. | UL 94 V2 | MARANYL or Equivalent | Brown |
| | 154719-6 | As Drg. | UL 94 V2 | MARANYL or Equivalent | Blue |
| | 154719-5 | As Drg. | UL 94 V2 | MARANYL or Equivalent | Green |
| | 154719-4 | As Drg. | UL 94 V2 | MARANYL or Equivalent | Yellow |
| | 154719-2 | As Drg. | UL 94 V2 | MARANYL or Equivalent | Red |
| | 154719-1 | As Drg. | UL 94 V2 | MARANYL or Equivalent | Natural |
| | 154719 | As. Drg. | UL 94 V2 | MARANYL or Equivalent | Black |
| Notes | Part Number | Part Revision | Flammability Rating | Material | Colour |

| | | | | | | | |
|------------|--|---------------------------------------|--|------------------|-----------|--|--|
| DIMENSIONS | | TOLERANCES UNLESS OTHERWISE SPECIFIED | | OWN | 09MAY2002 | Tyco Electronics UK Ltd. Stamore, Middlesex, HA7 4RS. | |
| mm | | LINEAR ± 0.5 | | DESIGN | 09MAY2002 | Tyco Electronics | |
| See Table | | HOLE ± 0.1 | | DRW | 09MAY2002 | POSITIVE LOCK RECEPTACLE INSULATOR | |
| | | ANGLE ± 0.2 | | APPD | 09MAY2002 | PART NAME | |
| | | RADIUS ± 0.1 | | PRODUCED | 09MAY2002 | 108-3252 | |
| | | SURFACE FINISH | | APPLICATION SPEC | 114-2153 | SIZE | |
| | | TEXT | | WEIGHT | 0.5g | DRAWING NO | |
| | | | | CUSTOMER DRAWING | | A2 00779 | |
| | | | | | | SCALE | |
| | | | | | | 5:1 | |
| | | | | | | SHEET 1 OF 1 | |
| | | | | | | REV AV | |