



## Compact Flash Card Connector SLIM Type II

### SPECIFICATIONS

#### Materials

Insulator: LCP UL 94V-0 white color  
 Contacts: Brass  
 Pivot Shell: Stainless Steel  
 Mount Ear: Copper alloy (Tin plating overall)

#### Electrical

Insulation Resistance: 1000 M $\Omega$  min.  
 Contact Resistance: 40 m $\Omega$  max.  
 Current Rating: 1A max.

#### Contact Plating

Contact Area: Gold plating over  $\varnothing$ 0 Nickel  
 Solder Tail area: 100Tin/Lead plating over  $\varnothing$ 0 Nickel

( click on the drawing for a more detailed view )

## Order Information-----

**33CFA2 SS1 - 1 1 A**  
 1      2      3      4      5

### 1. Series No.

33CFA2:50 Pin Type II

### 3. Ejector

0: Without  
 1: Right, L=41.30mm  
 2: Left, L=41.30mm  
 3: Right, L=34.70mm  
 4: Left, L=34.70mm

### 4. Stand Off

1: 0mm  
 2: 1.2mm  
 3: 2.2mm

### 5. Board Mount

A: Standard type  
 B: Reverse type

### 2. Terminal Version

SS1: SMT SLIM type