

60620-5

TE Internal Number: 60620-5



.200" Centerline, 250 V, 13 A max.

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Contact
- Contact Diameter = 2.13 mm
- Packaging Method = Loose Piece
- Contact Type = Pin
- Wire Range = 0.50-2.00² [20-14] mm [AWG]

View all Features

 PIN, LOOSE PIECE, COMMERCIAL MATE N LOK (P 	DF, English) Additional Information: • Product Line Information
Catalog Pages/Data Sheets: • <u>REPRESENTATIVE TERMINALS AND CONNECTORS</u> • <u>SOFT_SHELL_PIN_SOCKET_CONNECTORS_STAN</u> (PDF, English)	
 Product Specifications: None Available Application Specifications: MATE-N-LOK Commercial Pin And Socket Contact MATE-N-LOK Commercial Pin and Socket Contact Instruction Sheets: MATE-N-LOK Contact and Housing Selection Char CAD Files: (CAD Format & Compression Information) 2D Drawing (DXF, Version S) 3D Model (IGES, Version S) 3D Model (STEP, Version S) 	<u>s</u> (PDF, Japanese)
<pre>Product Type Features: Product Type = Contact</pre>	Contact Related Features:
 Wire Insulation Diameter (mm [in]) = 2.54 – 3.30 [0.100 – 0.130] Connector Line = Commercial MATE-N-LOK Comment = Insertion Tools: No. 455830-1 (IS 7984); Extraction Tools: Pins- No. 1-305183-1 (IS 408-7158); Sockets- No. 1-305183-2(IS 408-7158); Pins and Sockets- No. 465644-1 (IS 408-7211) Electrical Characteristics: Voltage (VAC) = 250 Current Rating (Amps.) = 13 Termination Related Features: Solder Tail Contact Plating = Gold (30) Body Related Features: 	 Contact Type = Pin Contact Base Material = Brass Industry Standards: RoHS/ELV Compliance = RoHS compliant, ELV compliant Lead Free Solder Processes = Not relevant for lead free process RoHS/ELV Compliance History = Always was RoHS compliant Packaging Related Features: Packaging Method = Loose Piece Other: Brand = AMP