

640579-2

TE Internal Number: 640579-2



.165" Centerline, 250 V, 9 A max.



Always EU RoHS/ELV Compliant (Statement of

Compliance)

Product Highlights:

- Contact
- Packaging Method = Loose Piece
- Contact Type = Split Pin
- Wire Range = 0.12-0.24² [26-24] mm [AWG]
- Wire Insulation Diameter = .64 1.27 mm

View all Features

Documentation & Additional Information

Product Drawings:

• PIN, LOOSE PIECE, MR (PDF, English)

Catalog Pages/Data Sheets:

• SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG (PDF, English)

Product Specifications:

None Available

Application Specifications:

 Miniature Rectangular (MR) Contacts and Housings (PDF, English)

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version C)
- 3D Model (IGES, Version C)
- 3D Model (STEP, Version C)

Additional Information:

• Product Line Information

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Contact
- Wire Insulation Diameter (mm [in]) = 0.64 -1.27 [0.025 - 0.050]
- Connector Line = Mini Rectangular
- Material = Phosphor Bronze
- Comment = Contact Extraction Tool No. 455822-2 (IS 9570); Contact Insertion Tool No. 455830-1 (IS 7984)

Electrical Characteristics:

- Voltage (VAC) = 250
- Current Rating (Amps.) = 9

Termination Related Features:

Solder Tail Contact Plating = Select Gold [30]

Body Related Features:

- Wire Range (mm [AWG]) = 0.12-0.24² [26-
- Contact Diameter (mm [in]) = 1.73 [0.068]
- Stock Thickness (mm [in]) = 0.20 [0.008]

Contact Related Features:

Contact Type = Split Pin

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

Packaging Method = Loose Piece

Other:

Brand = AMP